



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

## General Information

Extended Product Type:	TA200DU-200
Product ID:	1SAZ421201R1006
EAN:	4013614286063
Catalog Description:	TA200DU-200 Thermal Overload Relay
Long Description:	The TA200DU-200 thermal overload relay is an economic electromechanical protection device for the main circuit. It offers reliable and fast protection for motors in the event of overload or phase failure. The device has trip class 10A. Further features are the temperature compensation, trip contact (NC), signal contact (NO), automatic- or manual reset selectable, trip-free mechanism, STOP- and Test function and a trip indication. The overload relays are connected directly to the block contactors. Single mounting kits are available as accessory.

## Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Thermal Overload Relays

## Ordering

EAN:	4013614286063
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364900

## Dimensions

Product Net Width:	104 mm
Product Net Height:	151 mm
Product Net Depth:	126 mm
Product Net Weight:	0.785 kg

## Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	165 mm
Package Level 1 Height:	133 mm
Package Level 1 Length:	151 mm
Package Level 1 Gross Weight:	1.035 kg
Package Level 2 Units:	4 piece
Package Level 2 Width:	280 mm
Package Level 2 Height:	210 mm
Package Level 2 Length:	395 mm
Package Level 2 Gross Weight:	8.786 kg
Package Level 2 EAN:	4013614494284

## Technical

Setting Range:	150 ... 200 A
Rated Operational Voltage:	Auxiliary Circuit 440 V DC Auxiliary Circuit 500 V AC Main Circuit 690 V AC
Rated Operational Current ( $I_e$ ):	200 A
Rated Operational Current AC-3 ( $I_e$ ):	200 A
Rated Frequency (f):	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC Main Circuit 60 Hz Main Circuit 50 Hz Main Circuit DC
Rated Impulse Withstand Voltage ( $U_{imp}$ ):	Auxiliary Circuit 6 kV Main Circuit 6 kV
Rated Insulation Voltage ( $U_i$ ):	690 V
Number of Poles:	3
Number of Auxiliary Contacts NC:	1
Number of Auxiliary Contacts NO:	1
Number of Protected Poles:	3
Conventional Free-air Thermal Current ( $I_{th}$ ):	Auxiliary Circuit NC 10 A Auxiliary Circuit NO 6 A
Rated Operational Current AC-15 ( $I_e$ ):	(120 V) NC 3 A (120 V) NO 1.5 A

	(240 V) NC 3 A (240 V) NO 1.5 A (400 V) NC 1.9 A (400 V) NO 1 A (440 V) NC 1 A (440 V) NO 1 A (500 V) NC 1 A (500 V) NO 1 A
<b>Rated Operational Current DC-13 (I<sub>e</sub>):</b>	(125 V) NC 0.25 A (125 V) NO 0.25 A (24 V) NC 1.25 A (24 V) NO 1.25 A (250 V) NC 0.12 A (250 V) NO 0.04 A (60 V) NC 0.25 A (60 V) NO 0.25 A
<b>Degree of Protection:</b>	Housing IP20 Main Circuit Terminals IP00
<b>Pollution Degree:</b>	3
<b>Connecting Capacity-Auxiliary Circuit:</b>	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup> Flexible 1/2x 0.75 ... 2.5 mm <sup>2</sup> Rigid 1/2x 0.75 ... 4 mm <sup>2</sup>
<b>Connecting Capacity-Main Circuit:</b>	Hole Diameter > 10 mm <sup>2</sup> Rigid or Flexible with Cable Lug 1x 25 ... 120 mm <sup>2</sup>
<b>Tightening Torque:</b>	Auxiliary Circuit 1 ... 1.3 N·m Main Circuit 25 N·m
<b>Wire Stripping Length:</b>	Auxiliary Circuit 9 mm
<b>Recommended Screw Driver:</b>	Auxiliary Circuit Pozidriv 2 Main Circuit Open Bars
<b>Mounting Position:</b>	Position 1 to 6
<b>Power Loss:</b>	at Rated Operating Conditions per Pole 4.3 ... 7.7 W
<b>Suitable For:</b>	A145 A185 AF145 AF185 AF190 AF205
<b>Standards:</b>	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1

## Environmental

<b>Ambient Air Temperature:</b>	Operation -25 ... +55 °C Operation Compensated -25 ... +55 °C Storage -40 ... +70 °C
<b>Ambient Air Temperature Compensation:</b>	Yes
<b>Maximum Operating Altitude Permissible:</b>	2000 m
<b>Resistance to Shock acc. to IEC 60068-2-27:</b>	11 ms Pulse 12g
<b>RoHS Status:</b>	Following EU Directive 2002/95/EC August 18, 2005 and amendment

## Technical UL/CSA

<b>Maximum Operating Voltage UL/CSA:</b>	Main Circuit 600 V AC
<b>Ampere Rating UL/CSA:</b>	200 A
<b>Contact Rating UL/CSA:</b>	(NO:) B600 (NC:) C600
<b>Connecting Capacity Main Circuit UL/CSA:</b>	Flexible 1x 4 ... 0000 AWG Stranded 1x 4 ... 0000 AWG
<b>Connecting Capacity Auxiliary Circuit UL/CSA:</b>	Flexible 1/2x 18 ... 14 AWG Stranded 1/2x 18 ... 14 AWG
<b>Tightening Torque UL/CSA:</b>	Auxiliary Circuit 12 in·lb Main Circuit 220 in·lb

## Certificates and Declarations (Document Number)

<b>ABS Certificate:</b>	1SAA941000-0102
<b>BV Certificate:</b>	1SAA941000-0201
<b>CB Certificate:</b>	1SAA941004-2003
<b>CCC Certificate:</b>	1SAA941001-3803

<b>cUL Certificate:</b>	cUL_E48139
<b>Declaration of Conformity - CE:</b>	1SAD938511-0043
<b>DNV Certificate:</b>	1SAA941000-0303
<b>EAC Certificate:</b>	1SAA941002-2701
<b>GL Certificate:</b>	1SAA941000-0403 1SAA941006-0403
<b>GOST Certificate:</b>	1SAA941000-2704
<b>LR Certificate:</b>	1SAA941000-0504
<b>RMRS Certificate:</b>	1SAA941000-0703
<b>RoHS Information:</b>	1SAA941003-4404
<b>UL Certificate:</b>	UL_E48139 1SAA938001-1604

**Classifications**

<b>Object Classification Code:</b>	F
<b>eClass:</b>	7.0 27371501
<b>E-nummer:</b>	3228710
<b>ETIM 4:</b>	EC000106 - Thermal overload relay
<b>ETIM 5:</b>	EC000106 - Thermal overload relay
<b>UNSPSC:</b>	39121521





**Automatización Eléctrica**  
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
TA200DU-200 Thermal Overload Relay	1SAZ421201R1006	TA200DU200 200	<a href="#">Buy on EAN</a>