



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	UA26-30-10RA 48V 50Hz / 48V 60Hz
Product ID:	1SBL241024R8310
EAN:	3471522301833
Catalog Description:	UA26-30-10RA 48V 50Hz / 48V 60Hz Contactor
Long Description:	UA26..RA 3-pole contactors for capacitor switching, can be used in installations in which the peak current far exceeds 100 times nominal rms current. The contactors are delivered complete with their damping resistors and must be used without additional inductances (see table below). The capacitors must be discharged (maximum residual voltage at terminals ≤ 50 V) before being re-energized when the contactors are making. Their electrical durability is 250 000 operating cycles for $U_e < 500$ V and 100 000 operating cycles for 500 V $\leq U_e \leq 690$ V. The UA..RA contactors are fitted with a special front mounted block, which ensures the serial insertion of 3 damping resistors into the circuit to limit the current peak on energization of the capacitor bank. Their connection also ensures capacitor precharging in order to limit the second current peak occurring upon making of the main poles. The insertion of resistors allows to damp the highest current peak of the capacitor when switching on, whatever its level. The UA..RA series 3-pole contactors are of the block type design. - Main poles and auxiliary contacts: 3 main poles, 1 built-in auxiliary contact - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Block Contactors

Ordering

EAN:	3471522301833
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85369085

Dimensions

Product Net Width:	54 mm
Product Net Depth:	126.3 mm
Product Net Height:	120 mm
Product Net Weight:	0.710 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	135 mm
Package Level 1 Length:	155 mm
Package Level 1 Height:	63 mm
Package Level 1 Gross Weight:	0.71 kg
Package Level 1 EAN:	3471522301833
Package Level 2 Units:	63 piece

Technical

Number of Main Contacts NO:	3
Number of Main Contacts NC:	0
Number of Auxiliary Contacts NO:	1
Number of Auxiliary Contacts NC:	0
Rated Operational Voltage:	Main Circuit 690 V Auxiliary Circuit 690 V
Rated Frequency (f):	Supply Circuit 50 Hz Supply Circuit 60 Hz
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-5-1, $q = 40$ °C 16 A
Rated Operational Current AC-15 (I_e):	(220 / 240 V) 4 A (24 / 127 V) 6 A (380 / 440 V) 3 A (500 V) 2 A (690 V) 2 A
Short-Circuit Protective Devices:	Auxiliary Circuit - gG Type Fuses 10 A gG Type Fuses 125 A
Rated Short-time Withstand Current (I_{cw}):	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 210 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 45 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 90 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 400 A

	at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 110 A for 0.1 s 140 A for 1 s 100 A
Maximum Breaking Capacity:	cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 440 V 420 A cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 690 V 170 A
Maximum Electrical Switching Frequency:	240 cycles per hour
Rated Operational Current DC-13 (I_e):	(125 V) 1.1 / 138 A (24 V) 6 / 144 A (250 V) 0.55 / 138 A (48 V) 2.8 / 134 A (72 V) 2 / 144 A
Rated Insulation Voltage (U_i):	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp}):	8 kV
Coil Operating Limits:	(acc. to IEC 60947-4-1) 0.85 ... 1.1 x U _c (at θ ≤ 55 °C) °C
Rated Control Circuit Voltage (U_c):	50 Hz 48 V 60 Hz 48 V
Coil Consumption:	Average Holding Value 50 / 60 Hz 12 V·A Average Holding Value 50 / 60 Hz 3 W Average Holding Value 50 Hz 12 V·A Average Holding Value 50 Hz 3 W Average Holding Value 60 Hz 12 V·A Average Holding Value 60 Hz 3 W Average Pull-in Value 50 Hz 120 V·A Average Pull-in Value 60 Hz 140 V·A
Operate Time:	Between Coil Energization and NO Contact Closing 8 ... 21 ms Between Coil De-energization and NO Contact Opening 4 ... 11 ms
Connecting Capacity-Auxiliary Circuit:	Rigid Cable 1 ... 4 mm ² Flexible with Cable End 0.75 ... 2.5 mm ²
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20
Connecting terminals (delivered in open position) Main poles:	M 4 (+,-) pozidriv 2 screws with cable clamp
Terminal Type:	Screw Terminals

Environmental

Ambient Air Temperature:	Near Contactor for Operation in Free Air (0.85 ... 1.1 U _c) -40 ... +55 °C Near Contactor for Operation in Free Air (U _c) -40 ... +70 °C Close to Contactor for Storage -60 ... +80 °C
Climatic Withstand:	acc. to IEC 60068-2-30 and 60068-2-11 - UTE C 63-100 specification II
Maximum Operating Altitude Permissible:	3000 m
RoHS Status:	No declaration needed

Certificates and Declarations (Document Number)

CB Certificate:	CB_FR3447_60016915-509739B
CSA Certificate:	CSA_1033838_LR056745
Declaration of Conformity - CE:	1SBD250846C2000
EAC Certificate:	EAC_RU C-FR ME77 B01010
GOST Certificate:	GOST_POCCFRME77B07175
RoHS Information:	1SBC101059D0201

Classifications

ETIM 5:	EC001079 - Capacitor magnet contactor
UNSPSC:	39121529







Automatización Eléctrica
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
UA26-30-10RA 48V 50Hz / 48V 60Hz Contactor	1SBL241024R8310	UA26-30-10RA	Buy on EAN