



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

## General Information

<b>Extended Product Type:</b>	AF80-40-00-14
<b>Product ID:</b>	1SBL397201R1400
<b>EAN:</b>	3471523133747
<b>Catalog Description:</b>	AF80-40-00-14 250-500V50/60HZ-DC Contactor
<b>Long Description:</b>	AF80 4-pole contactors are used for controlling power circuits up to 690 V AC and 440 V DC. They are mainly used for controlling non-inductive or slightly inductive loads (i.e. resistance furnaces...). AF... contactors include an electronic coil interface accepting a wide control voltage $U_c$ min. ... $U_c$ max. Only four coils cover control voltages between 24...500 V 50/60 Hz or 20...500 V DC. AF contactors can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any coil change. AF contactors have built-in surge protection and do not require additional surge suppressors. The AF... series 4-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 4 N.O. main poles, front and side-mounted add-on auxiliary contact blocks (mechanically-linked auxiliary contacts compliant with Annex L of IEC 60947-5-1. N.C. mirror contacts compliant with Annex F of IEC 60947-4-1) - Control circuit: AC or DC operated - Accessories: a wide range of accessories is available.

## Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Block Contactors

## Ordering

<b>EAN:</b>	3471523133747
<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85369085

## Dimensions

<b>Product Net Width:</b>	90 mm
<b>Product Net Depth:</b>	116 mm
<b>Product Net Height:</b>	125.5 mm
<b>Product Net Weight:</b>	1.44 kg

## Container Information

<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Width:</b>	150 mm
<b>Package Level 1 Length:</b>	150 mm
<b>Package Level 1 Height:</b>	103 mm
<b>Package Level 1 Gross Weight:</b>	1.57 kg
<b>Package Level 1 EAN:</b>	3471523133747

## Technical

<b>Number of Main Contacts NO:</b>	4
<b>Number of Main Contacts NC:</b>	0
<b>Number of Auxiliary Contacts NO:</b>	0
<b>Number of Auxiliary Contacts NC:</b>	0
<b>Rated Operational Voltage:</b>	Main Circuit 690 V
<b>Rated Frequency (f):</b>	Main Circuit 50 / 60 Hz
<b>Conventional Free-air Thermal Current (<math>I_{th}</math>):</b>	acc. to IEC 60947-4-1, Open Contactors $q = 40^\circ\text{C}$ 125 A
<b>Rated Operational Current AC-1 (<math>I_e</math>):</b>	(690 V) $40^\circ\text{C}$ 125 A (690 V) $60^\circ\text{C}$ 105 A (690 V) $70^\circ\text{C}$ 90 A
<b>Rated Operational Current AC-3 (<math>I_e</math>):</b>	(220 / 230 / 240 V) $60^\circ\text{C}$ 80 A (380 / 400 V) $60^\circ\text{C}$ 80 A (415 V) $60^\circ\text{C}$ 80 A (440 V) $60^\circ\text{C}$ 80 A (500 V) $60^\circ\text{C}$ 65 A (690 V) $60^\circ\text{C}$ 49 A
<b>Rated Operational Power AC-3 (<math>P_e</math>):</b>	(220 / 230 / 240 V) 22 kW (380 / 400 V) 37 kW (415 V) 45 kW (440 V) 45 kW (500 V) 45 kW (690 V) 45 kW
<b>Rated Short-time Withstand Current (<math>I_{cw}</math>):</b>	at $40^\circ\text{C}$ Ambient Temp, in Free Air, from a Cold State 10 s 780 A at $40^\circ\text{C}$ Ambient Temp, in Free Air, from a Cold State 15 min 140 A

	at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 300 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1200 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 450 A
<b>Maximum Electrical Switching Frequency:</b>	AC-1 600 cycles per hour
<b>Rated Insulation Voltage (U<sub>i</sub>):</b>	acc. to UL/CSA 600 V acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V
<b>Rated Impulse Withstand Voltage (U<sub>imp</sub>):</b>	8 kV
<b>Maximum Mechanical Switching Frequency:</b>	3600 cycles per hour
<b>Rated Control Circuit Voltage (U<sub>c</sub>):</b>	50 Hz 250 ... 500 V 60 Hz 250 ... 500 V DC Operation 250 ... 500 V
<b>Connecting Capacity-Main Circuit:</b>	Flexible with Ferrule 1/2x 6...50 mm <sup>2</sup> Rigid 1x 6...70 mm <sup>2</sup> Rigid 2x 6...50 mm <sup>2</sup>
<b>Connecting Capacity-Control Circuit:</b>	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup> Rigid 1/2x 1...2.5 mm <sup>2</sup>
<b>Wire Stripping Length:</b>	Main Circuit 17 mm
<b>Degree of Protection:</b>	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
<b>Terminal Type:</b>	Screw Terminals

## Environmental

<b>Ambient Air Temperature:</b>	Close to Contactor for Storage -60...+80 °C Near Contactor for Operation in Free Air -40 ... +70 °C
<b>Maximum Operating Altitude Permissible:</b>	3000 m

## Technical UL/CSA

<b>General Use Rating UL/CSA:</b>	(600 V AC) 105 A
<b>Horsepower Rating UL/CSA:</b>	(120 V AC) Single Phase 7-1/2 Hp (240 V AC) Single Phase 15 Hp (200 ... 208 V AC) Three Phase 25 Hp (220 ... 240 V AC) Three Phase 30 Hp (440 ... 480 V AC) Three Phase 60 Hp (550 ... 600 V AC) Three Phase 75 Hp

## Certificates and Declarations (Document Number)

<b>ABS Certificate:</b>	ABS_15-GE1349500-PDA_90682247
<b>CB Certificate:</b>	CB_SE_77417
<b>Declaration of Conformity - CE:</b>	1SBD250182C1000
<b>LR Certificate:</b>	LRS_1300087E1
<b>RMRS Certificate:</b>	RMRS_1400682124

## Classifications

<b>ETIM 5:</b>	EC000066 - Magnet contactor, AC-switching
<b>UNSPSC:</b>	39121529





**Automatización Eléctrica**  
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
AF80-40-00-14 250-500V50/60HZ-DC Contactor	1SBL397201R1400	AF80-40-00-14	<a href="#">Buy on EAN</a>