



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	CA4-40N
Product ID:	1SBN010140R1240
EAN:	3471523130265
Catalog Description:	CA4-40N Auxiliary Contact Block
Long Description:	CA4-40N Auxiliary Contact Block

Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Block Contactors Accessories

Ordering

EAN:	3471523130265
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85389099

Dimensions

Product Net Weight:	0.055 kg
---------------------	----------

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	46 mm
Package Level 1 Height:	46 mm
Package Level 1 Length:	46 mm
Package Level 1 Gross Weight:	0.055 kg
Package Level 1 EAN:	3471523130265
Package Level 2 Units:	192 piece
Package Level 3 Units:	4608 piece
Product Packing Type:	Box

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2008 Q1
--------------	---

Technical UL/CSA

Tightening Torque UL/CSA:	Auxiliary Circuit 11 in·lb
---------------------------	----------------------------

Additional Information

Connecting Capacity-Auxiliary Circuit:	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid 1/2x 1...2.5 mm ²
Conventional Free-air Thermal Current (I _{th}):	acc. to IEC 60947-5-1, q = 40 °C 16 A
IIT Publishing Status:	Level 0 - Information enabled
Maximum Electrical Switching Frequency:	AC-15 1200 cycles per hour DC-13 900 cycles per hour
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Mounted Auxiliary Contacts:	4 NO, 0 NC
Number of Auxiliary Contacts NC:	0
Number of Auxiliary Contacts NO:	4
Product Main Type:	Accessories for Block Contactors
Product Name:	Auxiliary Contact Block
Rated Frequency (f):	Auxiliary Circuit 50 / 60 Hz
Rated Impulse Withstand Voltage (U _{imp}):	6 kV
Rated Insulation Voltage (U _i):	acc. to UL/CSA 600 V acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V
Rated Operational Current AC-15 (I _e):	(220 / 240 V) 4 A (24 / 127 V) 6 A (400 / 440 V) 3 A (500 V) 2 A (690 V) 2 A
Rated Operational Current DC-13	(110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W

(I_e): (220 V) 0.27 A / 60 W
(24 V) 6 A / 144 W
(250 V) 0.27 A / 68 W
(400 V) 0.15 A / 60 W
(48 V) 2.8 A / 134 W
(500 V) 0.13 A / 65 W
(600 V) 0.1 A / 60 W
(72 V) 1 A / 72 W

Rated Operational Voltage: Auxiliary Circuit 24 ... 690 V

Rated Short-time Withstand Current (I_{cw}): for 0.1 s 140 A
for 1 s 100 A

RoHS Date: 20090609

Suitable For: NF

Terminal Type: Screw Terminals

Tightening Torque: Auxiliary Circuit 1.2 N·m

Wire Stripping Length: Auxiliary Circuit 10 mm

Certificates and Declarations (Document Number)

ABS Certificate: ABS_15-GE1349500-PDA_90682247

CB Certificate: CB_SE_70922A2

CCC Certificate: CCC_2013010304651497

cUL Certificate: UL_20091128-E252354-3-1

Data Sheet, Technical Information: 1SBC100173C0201

Declaration of Conformity - CE: 1SBD250167C2000

EAC Certificate: EAC_RU C-FR ME77 B01048

GOST Certificate: GOST_POCCFR.ME77.B07174.pdf

LR Certificate: LRS_1300087E1

RINA Certificate: RINA_ELE084013XG

RMRS Certificate: RMRS_1300133124

RoHS Information: 1SBD251010E1000

Classifications

E-nummer: 3211428

ETIM 4: EC002498 - Accessories for low-voltage switch technology

ETIM 5: EC002498 - Accessories for low-voltage switch technology

Object Classification Code: K

UNSPSC: 39121500





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
CA4-40N Auxiliary Contact Block	1ISBN010140R1240	CA4-40N	Buy on EAN