



Automatización Eléctrica Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

IPSZ1D11



Extended Product Type:	IPSZ1D11				
Product ID:	1SBV002109R1411				
EAN:	1SBV002109R1411 3471522009586				
Catalog Description:	IPSZ1D11 Foot Switch				
Long Description:	IPSZIDTI Foot Switch				
Categories					
Products » Low Voltage Products and	d Systems » Control Products » Sensors » Limit Switches				
Drdering					
EAN:	3471522009586				
Minimum Order Quantity:	1 piece				
Customs Tariff Number:	85369085				
Dimensions					
Product Net Weight:	0.800 kg				
Container Information					
Package Level 1 Units:	1 piece				
Package Level 1 Width:	290 mm				
Package Level 1 Height:	165 mm				
Package Level 1 Length:	160 mm				
Package Level 1 Gross Weight:	0.8 kg				
Package Level 1 EAN:	3471522009586				
Environmental					
Ambient Air Temperature:	Operation -10 +70 °C				
	Storage -30 +80 °C				
Resistance to Shock acc. to IEC 60068-2-27:	Half-sine Pulse for 11 ms, No Change in Contact Position 50 m/s ²				
Resistance to Vibrations acc. to IEC 60068-2-6:	25g (10 to 500 Hz) no change in position of contacts greater than 100 μs				
00000-2-0.					
Technical UL/CSA					
Pilot Duty of Contact Elements acc.					
UL508:	Q600				
Flammability According to UL94:	V0				
Additional Information					
Action Type of the Contact Element	non-overlapping slow action contacts				
Action Type of the Contact Element (acc. to IEC 60947-5-1):					
Action Type of the Contact Element (acc. to IEC 60947-5-1): Actuation Torque:	acc. to IEC 60947-5-1 Min. 0.25 N·m				
Action Type of the Contact Element (acc. to IEC 60947-5-1): Actuation Torque: Base Color:	acc. to IEC 60947-5-1 Min. 0.25 N·m Grey				
Action Type of the Contact Element (acc. to IEC 60947-5-1): Actuation Torque: Base Color: Cable Outlets Per Side:	acc. to IEC 60947-5-1 Min. 0.25 N·m Grey 1 pre-pressed Pg16 knockout on each side				
Action Type of the Contact Element (acc. to IEC 60947-5-1): Actuation Torque: Base Color: Cable Outlets Per Side: Climatic Withstand:	acc. to IEC 60947-5-1 Min. 0.25 N·m Grey 1 pre-pressed Pg16 knockout on each side according to IEC 68-2-3 and salty mist according to IEC 68-2-11				
Action Type of the Contact Element (acc. to IEC 60947-5-1): Actuation Torque: Base Color: Cable Outlets Per Side: Climatic Withstand:	acc. to IEC 60947-5-1 Min. 0.25 N·m Grey 1 pre-pressed Pg16 knockout on each side				
Action Type of the Contact Element (acc. to IEC 60947-5-1): Actuation Torque: Base Color: Cable Outlets Per Side: Climatic Withstand: Connecting Capacity: Connecting terminals (delivered in	acc. to IEC 60947-5-1 Min. 0.25 N·m Grey 1 pre-pressed Pg16 knockout on each side according to IEC 68-2-3 and salty mist according to IEC 68-2-11 AWG 20 AWG 14				
Action Type of the Contact Element (acc. to IEC 60947-5-1): Actuation Torque: Base Color: Cable Outlets Per Side: Climatic Withstand: Connecting Capacity: Connecting terminals (delivered in open position): Contact Element Form (acc. to IEC	acc. to IEC 60947-5-1 Min. 0.25 N·m Grey 1 pre-pressed Pg16 knockout on each side according to IEC 68-2-3 and salty mist according to IEC 68-2-11 AWG 20 AWG 14 0.5 2.5 mm ²				
Action Type of the Contact Element (acc. to IEC 60947-5-1): Actuation Torque: Base Color: Cable Outlets Per Side: Climatic Withstand: Connecting Capacity: Connecting terminals (delivered in open position): Contact Element Form (acc. to IEC 60947-5-1): Conventional Free-air Thermal	acc. to IEC 60947-5-1 Min. 0.25 N·m Grey 1 pre-pressed Pg16 knockout on each side according to IEC 68-2-3 and salty mist according to IEC 68-2-11 AWG 20 AWG 14 0.5 2.5 mm ² M3.5 (+,-) screw Phillips head n 1 with captive cable gland				
Action Type of the Contact Element (acc. to IEC 60947-5-1): Actuation Torque: Base Color: Cable Outlets Per Side: Climatic Withstand: Connecting Capacity: Connecting terminals (delivered in open position): Contact Element Form (acc. to IEC 60947-5-1): Conventional Free-air Thermal Current (I _{th}):	acc. to IEC 60947-5-1 Min. 0.25 N·m Grey 1 pre-pressed Pg16 knockout on each side according to IEC 68-2-3 and salty mist according to IEC 68-2-11 AWG 20 AWG 14 0.5 2.5 mm ² M3.5 (+,-) screw Phillips head n 1 with captive cable gland Zb				
Action Type of the Contact Element (acc. to IEC 60947-5-1): Actuation Torque: Base Color: Cable Outlets Per Side: Climatic Withstand: Connecting Capacity: Connecting terminals (delivered in open position): Contact Element Form (acc. to IEC 60947-5-1): Conventional Free-air Thermal Current (I _{th}): Cover Color:	acc. to IEC 60947-5-1 Min. 0.25 N·m Grey 1 pre-pressed Pg16 knockout on each side according to IEC 68-2-3 and salty mist according to IEC 68-2-11 AWG 20 AWG 14 0.5 2.5 mm ² M3.5 (+,-) screw Phillips head n 1 with captive cable gland Zb acc. to IEC 60947-5-1, q = 40 °C 10.0 A				
Action Type of the Contact Element (acc. to IEC 60947-5-1): Actuation Torque: Base Color: Cable Outlets Per Side: Climatic Withstand: Connecting Capacity: Connecting terminals (delivered in open position): Contact Element Form (acc. to IEC 60947-5-1): Conventional Free-air Thermal Current (I _{th}): Cover Color: Degree of Protection: Electrical Shock Protection acc. to	acc. to IEC 60947-5-1 Min. 0.25 N·m Grey 1 pre-pressed Pg16 knockout on each side according to IEC 68-2-3 and salty mist according to IEC 68-2-11 AWG 20 AWG 14 0.5 2.5 mm ² M3.5 (+,-) screw Phillips head n 1 with captive cable gland Zb acc. to IEC 60947-5-1, q = 40 °C 10.0 A red				
Action Type of the Contact Element (acc. to IEC 60947-5-1): Actuation Torque: Base Color: Cable Outlets Per Side: Climatic Withstand: Connecting Capacity: Connecting terminals (delivered in open position): Contact Element Form (acc. to IEC 60947-5-1): Conventional Free-air Thermal Current (I _{th}): Cover Color: Degree of Protection: Electrical Shock Protection acc. to IEC 536:	acc. to IEC 60947-5-1 Min. 0.25 N·m Grey 1 pre-pressed Pg16 knockout on each side according to IEC 68-2-3 and salty mist according to IEC 68-2-11 AWG 20 AWG 14 0.5 2.5 mm ² M3.5 (+,-) screw Phillips head n 1 with captive cable gland Zb acc. to IEC 60947-5-1, q = 40 °C 10.0 A red acc. to IEC 60529 IP65				
Action Type of the Contact Element (acc. to IEC 60947-5-1): Actuation Torque: Base Color: Cable Outlets Per Side: Climatic Withstand: Connecting Capacity: Connecting terminals (delivered in open position): Contact Element Form (acc. to IEC 60947-5-1): Conventional Free-air Thermal Current (I _{th}): Cover Color: Degree of Protection: Electrical Shock Protection acc. to IEC 536: IIT Publishing Status:	acc. to IEC 60947-5-1 Min. 0.25 N·m Grey 1 pre-pressed Pg16 knockout on each side according to IEC 68-2-3 and salty mist according to IEC 68-2-11 AWG 20 AWG 14 0.5 2.5 mm ² M3.5 (+,-) screw Phillips head n 1 with captive cable gland Zb acc. to IEC 60947-5-1, q = 40 °C 10.0 A red acc. to IEC 60529 IP65 Double insulation - Class II				
Action Type of the Contact Element (acc. to IEC 60947-5-1): Actuation Torque: Base Color: Cable Outlets Per Side: Climatic Withstand: Connecting Capacity: Connecting terminals (delivered in open position): Contact Element Form (acc. to IEC 60947-5-1): Conventional Free-air Thermal Current (I _{th}): Cover Color: Degree of Protection: Electrical Shock Protection acc. to IEC 536: IIT Publishing Status: Load Factor:	acc. to IEC 60947-5-1 Min. 0.25 N·m Grey 1 pre-pressed Pg16 knockout on each side according to IEC 68-2-3 and salty mist according to IEC 68-2-11 AWG 20 AWG 14 0.5 2.5 mm ² M3.5 (+,-) screw Phillips head n 1 with captive cable gland Zb acc. to IEC 60947-5-1, q = 40 °C 10.0 A red acc. to IEC 60529 IP65 Double insulation - Class II Level 0 - Information enabled				
Action Type of the Contact Element (acc. to IEC 60947-5-1): Actuation Torque: Base Color: Cable Outlets Per Side:	acc. to IEC 60947-5-1 Min. 0.25 N·m Grey 1 pre-pressed Pg16 knockout on each side according to IEC 68-2-3 and salty mist according to IEC 68-2-11 AWG 20 AWG 14 0.5 2.5 mm ² M3.5 (+,-) screw Phillips head n 1 with captive cable gland Zb acc. to IEC 60947-5-1, q = 40 °C 10.0 A red acc. to IEC 60529 IP65 Double insulation - Class II Level 0 - Information enabled .5				

Number of Auxiliary Contacts NC:	1			
Number of Auxiliary Contacts NO:	1			
Operating Angle of the Foot Switch Pedal:	15 °			
Operating Format:	free movement foot switch with half-red cover			
Positive Opening Operation of NC Contact(s):	Yes			
Product Main Type:	Foot Switches			
Product Name:	Foot Switch			
Rated Frequency (f):	Supply Circuit 50 Hz Supply Circuit 60 Hz			
Rated Impulse Withstand Voltage (U _{imp}):	6 kV			
Rated Insulation Voltage (Ui):	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V			
Rated Operational Current AC-15 (I _e):	(130 V) 5.5 A (230 V) 3.1 A (240 V) 3 A (24 V) 10 A (400 V) 1.8 A			
Rated Operational Current DC-13 (I _e):	(110 V) 0.6 / 66 A (24 V) 2.8 / 67.2 A (250 V) 0.27 / 67.5 A			
Resistance Between Contacts:	25 mΩ			
Standards:	IEC 60947-1, IEC 60947-5-1, EN 60947-1, EN 60947-5-1, UL 508 and CSA C22-2 N°14			
Terminal Marking:	according to EN 50013			

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SBC001699R1002
Declaration of Conformity - CE:	1SBD250882C2000

Classifications

ETIM 4:	EC001829 - Position switch modular
ETIM 5:	EC001829 - Position switch modular
UNSPSC:	39121500







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
IPSZ1D11 Foot Switch	1SBV002109R1411	IPSZ1D11	Buy on EAN