Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE

LS45P00D11

General Information

Extended Product Type:	LS45P00D11
Product ID:	1SBV012400R1411
EAN:	3471522616746
Catalog Description:	LS45P00D11 Limit Switch
Long Description:	LS45P00D11 Limit Switch

Categories

Products » Low Voltage Products and Systems » Control Products » Sensors » Limit Switches

Ordering

EAN:	3471522616746
Minimum Order Quantity:	10 piece
Customs Tariff Number:	85369085

Dimensions

Product Net Width:	40 mm
Product Net Weight:	0.108 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 EAN:	3471522616746

Environmental

Ambient Air Temperature:	Operation -25 … +70 °C Storage -30 … +80 °C
Resistance to Shock acc. to IEC 60068-2-27:	Half-sine Pulse for 11 ms, No Change in Contact Position 50 m/s²
Resistance to Vibrations acc. to IEC 60068-2-6:	25g (10 to 500 Hz) no change in position of contacts greater than 100 µs

Technical UL/CSA

Pilot Duty of Contact Elements acc. UL508:	A600 Q600
Flammability According to UL94:	V0

Additional Information

Action Type of the Contact Element (acc. to IEC 60947-5-1):	non-overlapping slow action contacts
Actuation Speed:	acc. to IEC 60947-5-1 Min. 0.06 m/s
Actuator Type:	without operating head
Angular Head Adjustment:	without operating head
Climatic Withstand:	according to IEC 68-2-3 and salty mist according to IEC 68-2-11 when an operating head is fitted on
Connecting Capacity:	AWG 20 ... AWG 14 0.5 ... 2.5 mm²
Connecting terminals (delivered in open position):	M3.5 (+,-) pozidriv 2 screw with cable clamp
Consistency (Measured over 1 Million Operations):	0.1 mm
Contact Element Form (acc. to IEC 60947-5-1):	Zb
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-5-1, q = 40 °C 10.0 A
Electrical Shock Protection acc. to IEC 536:	Double insulation - Class II
IIT Publishing Status:	Level 0 - Information enabled
Load Factor:	.5
Maximum Electrical Switching Frequency:	3600 cycles per hour
Mechanical Durability:	dependent on heads million
Mounting by Screws (not supplied):	2 or 4 x M5 screws
Mounting Position:	all positions are authorised
Number and Type of Bottom Cable	1/2 NPT cable gland

Glands:	
Number of Auxiliary Contacts NC:	1
Number of Auxiliary Contacts NO:	1
Positive Opening Operation of NC Contact(s):	Yes
Product Main Type:	LS40
Product Name:	Limit Switch
Rated Frequency (f):	Supply Circuit 50 Hz Supply Circuit 60 Hz
Rated Impulse Withstand Voltage (U_{imp}):	6 kV
Rated Insulation Voltage (U_i):	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V
Rated Operational Current AC-15 (I_e):	(130 V) 5.5 A (230 V) 3.1 A (240 V) 3 A (24 V) 10 A (400 V) 1.8 A
Rated Operational Current DC-13 (I_e):	(110 V) 0.6 / 66 A (24 V) 2.8 / 67.2 A (250 V) 0.27 / 67.5 A
Resistance Between Contacts:	25 mΩ
Standards:	IEC 60947-1, IEC 60947-5-1, EN 60947-1, EN 60947-5-1, UL 508 and CSA C22-2 N°14
Terminal Marking:	according to EN 50013

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SBC141127C0201
Declaration of Conformity - CE:	1SBD250881C2000

Classifications

ETIM 4:	EC001829 - Position switch modular
ETIM 5:	EC001829 - Position switch modular

Automatización Eléctrica
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
LS45P00D11 Limit Switch	1SBV012400R1411	LS45P00D11	Buy on EAN