



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	LS45M11L02
Product ID:	1SBV013111R1302
EAN:	3471522612625
Catalog Description:	LS45M11L02 Limit Switch
Long Description:	LS45M11L02 Limit Switch

Categories

Products » Low Voltage Products and Systems » Control Products » Sensors » Limit Switches

Ordering

EAN:	3471522612625
Minimum Order Quantity:	5 piece
Customs Tariff Number:	85369085

Dimensions

Product Net Width:	40 mm
Product Net Weight:	0.240 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	120 mm
Package Level 1 Height:	45 mm
Package Level 1 Length:	45 mm
Package Level 1 Gross Weight:	0.24 kg
Package Level 1 EAN:	3471522612625

Environmental

Ambient Air Temperature:	Operation -25 ... +70 °C Storage -30 ... +80 °C
Resistance to Shock acc. to IEC 60068-2-27:	Half-sine Pulse for 11 ms, No Change in Contact Position 50 m/s ²
Resistance to Vibrations acc. to IEC 60068-2-6:	25g (10 to 500 Hz) no change in position of contacts greater than 100 µs

Technical UL/CSA

Pilot Duty of Contact Elements acc. UL508:	A600 Q600
--	--------------

Additional Information

Action Type of the Contact Element (acc. to IEC 60947-5-1):	Simultaneous slow action contacts
Actuating Force:	Minimum Force acc. to IEC 60947-5-1 22 N
Actuation Speed:	acc. to IEC 60947-5-1 Max. 0.50 m/s acc. to IEC 60947-5-1 Min. 0.06 m/s
Actuator Type:	stainless steel plain plunger
Angular Head Adjustment:	adjustable head every 90°
Angular Lever Adjustment:	none
Climatic Withstand:	according to IEC 68-2-3 and salty mist according to IEC 68-2-11
Connecting Capacity:	AWG 20 ... AWG 14 0.5 ... 2.5 mm ²
Connecting terminals (delivered in open position):	M3.5 (+,-) pozidriv 2 screw with cable clamp
Consistency (Measured over 1 Million Operations):	0.05 mm
Contact Element Form (acc. to IEC 60947-5-1):	Zb
Conventional Free-air Thermal Current (I _{th}):	acc. to IEC 60947-5-1, q = 40 °C 10.0 A
Degree of Protection:	acc. to IEC 60529 IP66
Electrical Shock Protection acc. to IEC 536:	Class I
IIT Publishing Status:	Level 0 - Information enabled


Load Factor:	.5
Maximum Electrical Switching Frequency:	3600 cycles per hour
Mechanical Durability:	30 million
Mounting by Screws (not supplied):	2 or 4 x M5 screws
Mounting Position:	all positions are authorised
Movement to be Detected:	on end
Number and Type of Bottom Cable Glands:	1/2 NPT cable gland
Number of Auxiliary Contacts NC:	2
Operating Head Shape:	B shape acc. EN 50041
Positive Opening Operation Force (Direct Opening Action):	Minimum Force acc. to IEC 60947-5-1 66 N
Positive Opening Operation of NC Contact(s):	Yes
Product Main Type:	LS40
Product Name:	Limit Switch
Rated Frequency (f):	Supply Circuit 50 Hz Supply Circuit 60 Hz
Rated Impulse Withstand Voltage (U_{imp}):	6 kV
Rated Insulation Voltage (U_i):	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V
Rated Operational Current AC-15 (I_e):	(130 V) 5.5 A (230 V) 3.1 A (240 V) 3 A (24 V) 10 A (400 V) 1.8 A
Rated Operational Current DC-13 (I_e):	(110 V) 0.6 / 66 A (24 V) 2.8 / 67.2 A (250 V) 0.27 / 67.5 A
Resistance Between Contacts:	25 mΩ
Standards:	IEC 60947-1, IEC 60947-5-1, EN 60947-1, EN 60947-5-1, UL 508 and CSA C22-2 N°14
Terminal for Protective Conductor:	M 3.5 (+,-) pozidriv 2 screw with cable clamp
Terminal Marking:	according to EN 50013

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	AC1300
Declaration of Conformity - CE:	1SBD250881C2000

Classifications

ETIM 4:	EC001829 - Position switch modular
ETIM 5:	EC001829 - Position switch modular





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
LS45M11L02 Limit Switch	1SBV013111R1302	LS45M11L02	Buy on EAN