



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

# LS65M61C11



#### **General Information**

LS65M61C11 **Extended Product Type:** Product ID: 1SBV013361R1511 EAN: 3471522616180

**Catalog Description:** LS65M61C11 Limit Switch Long Description: LS65M61C11 Limit Switch

#### **Categories**

Products » Low Voltage Products and Systems » Control Products » Sensors » Limit Switches

#### Ordering

EAN: 3471522616180 **Minimum Order Quantity:** 5 piece **Customs Tariff Number:** 85369085

### **Dimensions**

**Product Net Width:** 60 mm **Product Net Weight:** 0.320 kg

## **Container Information**

Package Level 1 Units: 1 piece Package Level 1 Width: 200 mm Package Level 1 Height: 70 mm Package Level 1 Length: 65 mm Package Level 1 Gross Weight: 0.32 kg Package Level 1 EAN: 3471522616180

### **Environmental**

**Ambient Air Temperature:** Operation -25 ... +70 °C

Storage -30 ... +80 °C

Resistance to Shock acc. to IEC

60068-2-27:

Half-sine Pulse for 11 ms, No Change in Contact Position 50 m/s<sup>2</sup>

Resistance to Vibrations acc. to IEC 25g (10 to 500 Hz) no change in position of contacts greater than 100 µs 60068-2-6:

#### **Technical UL/CSA**

Pilot Duty of Contact Elements acc. A600 UL508: Q600

### Additional Information

Action Type of the Contact Element overlapping slow action contacts

(acc. to IEC 60947-5-1):

acc. to IEC 60947-5-1 Max. 1.50 m/s **Actuation Speed:** 

acc. to IEC 60947-5-1 Min. 0.06 m/s acc. to IEC 60947-5-1 Min. 0.15 N·m

**Actuation Torque: Actuator Type:** stainless steel flexible lever with insulated end

Angular Head Adjustment: adjustable head every 90°

9° in 9° Angular Lever Adjustment:

Climatic Withstand: according to IEC 68-2-3 and salty mist according to IEC 68-2-11

acc. to IEC 60529 IP66

**Connecting Capacity:** AWG 20 ... AWG 14

0.5 ... 2.5 mm<sup>2</sup>

open position):

Connecting terminals (delivered in M3.5 (+,-) pozidriv 2 screw with cable clamp

Consistency (Measured over 1

Million Operations):

0.05 mm

Contact Element Form (acc. to IEC

60947-5-1):

**Conventional Free-air Thermal** Current (Ith):

acc. to IEC 60947-5-1, q = 40 °C 10.0 A

Degree of Protection:

Class I

Electrical Shock Protection acc. to IEC 536:

**IIT Publishing Status:** Level 0 - Information enabled Load Factor: .5

**Maximum Electrical Switching** 

Frequency:

3600 cycles per hour

Mounting by Screws (not supplied): 2 x M5 screws

Mounting Position: all positions are authorised

Movement to be Detected: Fully Directional Translation Movement

Number and Type of Bottom Cable 1/2 NPT cable gland

Glands:

Number of Auxiliary Contacts NC: 1
Number of Auxiliary Contacts NO: 1
Positive Opening Operation of NC No

Contact(s):

Product Main Type: LS70
Product Name: Limit Switch

Rated Frequency (f): Supply Circuit 50 Hz Supply Circuit 60 Hz

Rated Impulse Withstand Voltage

(U<sub>imp</sub>):

Rated Insulation Voltage (Ui): acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V

acc. to UL/CSA 600 V

**Rated Operational Current AC-15** 

(l<sub>e</sub>):

(130 V) 5.5 A (230 V) 3.1 A (240 V) 3 A (24 V) 10 A (400 V) 1.8 A

6 kV

**Rated Operational Current DC-13** 

(l<sub>e</sub>):

(110 V) 0.6 / 66 A (24 V) 2.8 / 67.2 A (250 V) 0.27 / 67.5 A

Resistance Between Contacts:  $25 \text{ m}\Omega$ 

Standards: IEC 60947-5-1, EN 60947-5-1, EN 60947-5-1, UL 508 and CSA C22-2 N°14

**Terminal for Protective Conductor:** M 3.5 (+,-) pozidriv 2 screw with cable clamp

Terminal Marking: according to EN 50013

### **Certificates and Declarations (Document Number)**

Data Sheet, Technical Information: AC1300

Declaration of Conformity - CE: 1SBD250881C2000

### Classifications

ETIM 4: EC001829 - Position switch modular
ETIM 5: EC001829 - Position switch modular







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
LS65M61C11 Limit Switch	1SBV013361R1511	LS65M61C11	Buy on EAN