



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

OT63F4C



General Information

Extended Product Type: OT63F4C

Product ID: 1SCA105369R1001 **EAN:** 6417019393131

Catalog Description: OT63F4C CHANGE-OVER SWITCH

Long Description: Handle and shaft has to be ordered separately

Categories

Products » Low Voltage Products and Systems » Switches » Change-over and Transfer Switches » Manual Change-over Switches

Ordering

EAN: 6417019393131

Minimum Order Quantity: 1 piece
Customs Tariff Number: 85365080

Dimensions

Product Net Width: 140 mm

Product Net Height: 92 mm

Product Net Depth: 85 mm

Product Net Weight: 0.7 kg

Container Information

Package Level 1 Units: 1 piece
Package Level 1 Width: 102 mm
Package Level 1 Height: 103 mm
Package Level 1 Length: 205 mm
Package Level 1 Gross Weight: 0.76 kg
Package Level 1 EAN: 6417019393131

Environmental

RoHS Status: Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q4

Technical UL/CSA

Ampere Rating UL/CSA: 60 A

Horsepower Rating UL/CSA: (acc. to UL 200 V) 15 Hp

(acc. to UL 208 V) 15 Hp (acc. to UL 240 V) 15 Hp (acc. to UL 480 V) 30 Hp (acc. to UL 600 V) 30 Hp

Additional Information

Cable Cross-Section: $1.5...35 \text{ mm}^2$ Conventional Free-air Thermal $q = 40 \, ^{\circ}\text{C} 63 \, \text{A}$

Current (Ith):

Conventional Thermal Current (Ithe): Fully Enclosed 63 A

IIT Publishing Status: Level 0 - Information enabled

Number of Poles: 4

Operating Mechanism: Mechanism between the poles

Pollution Degree: 3

Position of Line Terminals: Top In - Bottom Out

Power Loss: 2.8 W Product Main Type: OT63_C

Product Name: CHANGE-OVER SWITCH

Rated Impulse Withstand Voltage 8 kV

(U_{imp}):

Rated Insulation Voltage (U_i): 750 V

Rated Operational Current AC-21A (500 V) 63 A (690 V) 63 A

Rated Operational Current AC-22A (I_e):

(500 V) 63 A (690 V) 63 A

Rated Operational Current AC-23A (380 ... 415 V) 45 A

(l_e): (500 V) 45 A (690 V) 20 A

Rated Operational Power AC-23A

(P_e):

(220 ... 240 V) 11 kW

(400 V) 22 kW (500 V) 22 kW (690 V) 15 kW

Rated Operational Voltage: 750 V

Rated Short-time Withstand Current for 1 s 1 kiloampere rms

(I_{cw}):

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:1SCC303003C0201Declaration of Conformity - CE:1SCC303020D0201RoHS Information:1SCC301183D0201

Classifications

ETIM 5: EC000216 - Switch disconnector

Object Classification Code: Q







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

| Product | Code | Reference | Product link |
|----------------------------|-----------------|-----------|--------------|
| OT63F4C CHANGE-OVER SWITCH | 1SCA105369R1001 | OT63F4C | Buy on EAN |