



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	OS800D04N2K
Product ID:	1SCA108722R1001
EAN:	6417019419510
Catalog Description:	OS800D04N2K Switch fuse
Long Description:	Including terminal bolt kit, a black Test-ON-OFF plastic handle and shaft as standard. The handle is padlockable in the OFF-position.

Categories

Products » Low Voltage Products and Systems » Switches » Switch Fuses

Ordering

EAN:	6417019419510
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Dimensions

Product Net Width:	431 mm
Product Net Height:	306 mm
Product Net Depth:	233 mm
Product Net Weight:	16 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	328 mm
Package Level 1 Height:	260 mm
Package Level 1 Length:	453 mm
Package Level 1 Gross Weight:	15.9 kg
Package Level 1 EAN:	6417019419510

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q4
--------------	---

Additional Information

Conventional Free-air Thermal Current (I_{th}):	$q = 40\text{ }^{\circ}\text{C}$ 800 A
Conventional Thermal Current (I_{the}):	Fully Enclosed 1000 A
Fuse Size:	3
Fuse System:	DIN
Fuse Type:	DIN
Handle Type:	Direct Handle
IIT Publishing Status:	Level 0 - Information enabled
Includes:	Handle and Shaft
Mounting Type:	Normal
Number of Poles:	4
Operating Mechanism:	Mechanism at the end of the switch
Operating Mode:	Front Operated
Order Multiple:	1 piece
Pollution Degree:	3
Position of Line Terminals:	Top In - Bottom Out
Power Loss:	75 W
Product Main Type:	OS800
Product Name:	Switch fuse
Rated Impulse Withstand Voltage (U_{imp}):	12 kV
Rated Insulation Voltage (U_i):	1000 V
Rated Operational Current AC-21A (I_e):	(500 V) 800 A (690 V) 800 A
Rated Operational Current AC-22A (I_e):	(380 ... 415 V) 800 A (500 V) 800 A (690 V) 800 A
Rated Operational Current AC-23A	(380 ... 415 V) 800 A

(I_e):	(500 V) 800 A (690 V) 800 A
Rated Operational Power AC-23A (P_e):	(220 ... 240 V) 250 kW (400 V) 450 kW (415 V) 450 kW (500 V) 560 kW (690 V) 710 kW
Rated Operational Voltage:	690 V AC
Rated Short-time Withstand Current (I_{cw}):	for 1 s 18 kiloampere rms
Standards:	IEC
Terminal Type:	Lug terminals

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SCC311013C0201
Declaration of Conformity - CE:	1SCC311113D0203

Classifications

ETIM 5:	EC001040 - Fuse switch disconnecter
Object Classification Code:	Q





Automatización Eléctrica
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
OS800D04N2K Switch fuse	1SCA108722R1001	OS800D04N2K	Buy on EAN