



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	OTM1000E3CM230C
Product ID:	1SCA112677R1001
EAN:	6417019453927
Catalog Description:	OTM1000E3CM230C MOTORIZED C/O SWITCH
Long Description:	Including a handle for manual operation, bolt kit with nut and washers for all terminals and male connectors for control circuits. Include a storage clip for the handle and spare fuses.

Categories

Products » Low Voltage Products and Systems » Switches » Change-over and Transfer Switches » Motorized Change-over Switches

Ordering

EAN:	6417019453927
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Dimensions

Product Net Width:	507 mm
Product Net Height:	306 mm
Product Net Depth:	297 mm
Product Net Weight:	55 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	440 mm
Package Level 1 Height:	565 mm
Package Level 1 Length:	700 mm
Package Level 1 Gross Weight:	55 kg
Package Level 1 EAN:	6417019453927

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q4
--------------	---

Additional Information

Conventional Free-air Thermal Current (I_{th}):	$q = 40\text{ }^{\circ}\text{C}$ 1000 A
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	3
Operating Mechanism:	Mechanism at the end of the switch
Pollution Degree:	3
Position of Line Terminals:	Top In - Bottom Out
Power Loss:	19 W
Product Main Type:	OTM1000_CM
Product Name:	MOTORIZED C/O SWITCH
Rated Impulse Withstand Voltage (U_{imp}):	12 kV
Rated Insulation Voltage (U_i):	1000 V
Rated Operational Current AC-21A (I_e):	(500 V) 1000 A (690 V) 1000 A
Rated Operational Current AC-22A (I_e):	(500 V) 1000 A (690 V) 1000 A
Rated Operational Current AC-23A (I_e):	(380 ... 415 V) 1000 A (500 V) 1000 A (690 V) 1000 A
Rated Operational Power AC-23A (P_e):	(230 V) Three Phase 315 kW (400 V) 560 kW (500 V) 710 kW (690 V) 1000 kW
Rated Operational Voltage:	1000 V
Rated Short-time Withstand Current (I_{cw}):	for 1 s 50 kiloampere rms

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SCC303003C0201
Declaration of Conformity - CE:	1SCC303027D0201
RoHS Information:	1SCC303036D0202

Classifications

ETIM 5:	EC000216 - Switch disconnecter
Object Classification Code:	Q





Automatización Eléctrica
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
OTM1000E3CM230C MOTORIZED C/O SWITCH	1SCA112677R1001	OTM1000E3CM230C	Buy on EAN