



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	OTM63F3CMA230V
Product ID:	1SCA120095R1001
EAN:	6417019516844
Catalog Description:	OTM63F3CMA230V MOTORIZED C/O SWITCH
Long Description:	Including a handle for manual operation, bolt kit with nut and washers for all terminals and male connectors for control circuits. Types OTM630...2500E_ include a storage clip for the handle and spare fuses.

Categories

Products » Low Voltage Products and Systems » Switches » Change-over and Transfer Switches » Motorized Change-over Switches

Ordering

EAN:	6417019516844
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Dimensions

Product Net Width:	230 mm
Product Net Height:	100 mm
Product Net Depth:	116 mm
Product Net Weight:	1.64 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	115 mm
Package Level 1 Height:	115 mm
Package Level 1 Length:	315 mm
Package Level 1 Gross Weight:	1.64 kg
Package Level 1 EAN:	6417019516844

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q4
--------------	---

Additional Information

Cable Cross-Section:	10-70 mm ²
Conventional Free-air Thermal Current (I_{th}):	$q = 40\text{ °C } 63\text{ A}$
Conventional Thermal Current (I_{the}):	Fully Enclosed 63 A
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	3
Operating Mechanism:	Mechanism at the end of the switch
Pollution Degree:	3
Position of Line Terminals:	Top In - Bottom Out
Power Loss:	2.8 W
Product Main Type:	OTM63_CM
Product Name:	MOTORIZED C/O SWITCH
Rated Impulse Withstand Voltage (U_{imp}):	8 kV
Rated Insulation Voltage (U_i):	800 V
Rated Operational Current AC-21A (I_e):	(500 V) 63 A (690 V) 63 A
Rated Operational Current AC-22A (I_e):	(500 V) 63 A (690 V) 63 A
Rated Operational Current AC-23A (I_e):	(380 ... 415 V) 63 A (500 V) 60 A (690 V) 40 A
Rated Operational Power AC-23A (P_e):	(220 ... 240 V) 15 kW (400 V) 30 kW (415 V) 30 kW (500 V) 37 kW (690 V) 37 kW

Rated Operational Voltage:	800 V
Rated Short-time Withstand Current (I_{cw}):	for 1 s 2.5 kiloampere rms

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SCC303003C0201
Declaration of Conformity - CE:	1SCC303039D0201
RoHS Information:	1SCC303036D0202

Classifications

ETIM 5:	EC000216 - Switch disconnecter
Object Classification Code:	Q





Automatización Eléctrica
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
OTM63F3CMA230V MOTORIZED C/O SWITCH	1SCA120095R1001	OTM63F3CMA230V	Buy on EAN