



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

### General Information

Extended Product Type:	T2H 160 PR221DS-LS In=160A 3p F F
Product ID:	1SDA051147R1
EAN:	8015644515690
Catalog Description:	T2H 160 PR221DS-LS In=160A 3p F F
Long Description:	C.BREAKER TMAX T2H 160 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC PR221DS-LS R 160

### Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Moulded Case Circuit Breakers » Tmax T

### Ordering

EAN:	8015644515690
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

### Dimensions

Product Net Width:	90 mm
Product Net Height:	130 mm
Product Net Depth:	70 mm
Product Net Weight:	1.12 kg

### Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	128 mm
Package Level 1 Height:	135 mm
Package Level 1 Length:	143 mm
Package Level 1 Gross Weight:	1.22 kg
Package Level 1 EAN:	8015644515690

### Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007-01-01
--------------	--

### Additional Information

Electrical Durability:	8000 cycle 120 cycles per hour
IIT Publishing Status:	Level 0 - Information enabled
Mechanical Durability:	25000 cycle 240 cycles per hour
Number of Poles:	3
Power Loss:	at Rated Operating Conditions per Pole 17 W
Product Main Type:	SACE Tmax T
Product Name:	Automatic Circuit Breaker
Product Type:	CB
Rated Current ( $I_n$ ):	160 A
Rated Impulse Withstand Voltage ( $U_{imp}$ ):	8 kV
Rated Insulation Voltage ( $U_i$ ):	800 V
Rated Operational Voltage:	690 V AC 500 V DC
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ ):	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 55 kA (500 V AC) 36 kA (690 V AC) 8 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ):	(220 V AC) 10 kA (230 V AC) 10 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA

(440 V AC) 55 kA  
(500 V AC) 36 kA  
(690 V AC) 8 kA  
(250 V DC) 2 Poles in Series 70 kA  
(250 V DC) 3 Poles in Series 85 kA  
(500 V DC) 3 Poles in Series 70 kA

**Rated Uninterrupted Current ( $I_u$ ):** 160 A

**Release Type:** EL

**Standards:** IEC 60947

**Sub-type:** T2

**Suitable For:** T2

**Suitable for Product Class:** Moulded Case Circuit Breakers

**Terminal Connection Type:** Fixed Circuit-Breakers  
Front

**Test Voltage at Industrial Frequency for 1 Minute:** 3000 V

**Test Voltage Max ( $U_{test}$ ):** 3000 V

**Version:** F

### Certificates and Declarations (Document Number)

**Data Sheet, Technical Information:** 1SDC210004D0203

**Data Sheet, Technical Information (Part 2):** 1SDM000030R0001

**Declaration of Conformity - CE:** 1SDL000165R0002

**GL Certificate:** 1SDL000163R0059

**RoHS Information:** 1SDL000200R0001

### Classifications

**Object Classification Code:** Q

**UNSPSC:** 39121100





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

<b>Product</b>	<b>Code</b>	<b>Reference</b>	<b>Product link</b>
T2H 160 PR221DS-LS In=160A 3p F F	1SDA051147R1	T2H160	<a href="#">Buy on EAN</a>