



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

T2S 160 PR221DS-I In=100A 4p F F



General Information

Extended Product Type:	T2S 160 PR221DS-I In=100A 4p F F
Product ID:	1SDA051182R1
EAN:	8015644516031
Catalog Description:	T2S 160 PR221DS-I In=100A 4p F F
Long Description:	C.BREAKER TMAX T2S 160 FIXED FOUR-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC PR221DS-I R 100

Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Moulded Case Circuit Breakers » Tmax T

Ordering

EAN:	8015644516031
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

Dimensions

Product Net Width:	120 mm
Product Net Height:	130 mm
Product Net Depth:	70 mm
Product Net Weight:	1.5 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	128 mm
Package Level 1 Height:	135 mm
Package Level 1 Length:	143 mm
Package Level 1 Gross Weight:	1.6 kg
Package Level 1 EAN:	8015644516031

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007-01-01
--------------	--

Additional Information

Electrical Durability:	8000 cycle 120 cycles per hour
IIT Publishing Status:	Level 0 - Information enabled
Mechanical Durability:	25000 cycle 240 cycles per hour
Number of Poles:	4
Power Loss:	at Rated Operating Conditions per Pole 8 W
Product Main Type:	SACE Tmax T
Product Name:	Automatic Circuit Breaker
Product Type:	CB
Rated Current (I_n):	100 A
Rated Impulse Withstand Voltage (U_{imp}):	8 kV
Rated Insulation Voltage (U_i):	800 V
Rated Operational Voltage:	690 V AC 500 V DC
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 45 kA (500 V AC) 30 kA (690 V AC) 7 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 8.5 kA (230 V AC) 8.5 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA

	(440 V AC) 45 kA (500 V AC) 30 kA (690 V AC) 7 kA (250 V DC) 2 Poles in Series 50 kA (250 V DC) 3 Poles in Series 55 kA (500 V DC) 3 Poles in Series 50 kA
Rated Uninterrupted Current (I _u):	160 A
Release Type:	EL
Standards:	IEC 60947
Sub-type:	T2
Suitable For:	T2
Suitable for Product Class:	Moulded Case Circuit Breakers
Terminal Connection Type:	Fixed Circuit-Breakers Front
Test Voltage at Industrial Frequency for 1 Minute:	3000 V
Test Voltage Max (U _{test}):	3000 V
Version:	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SDC210004D0203
Data Sheet, Technical Information (Part 2):	1SDM000030R0001
Declaration of Conformity - CE:	1SDL000165R0002
GL Certificate:	1SDL000163R0059
RoHS Information:	1SDL000200R0001

Classifications

Object Classification Code:	Q
UNSPSC:	39121100





Automatización Eléctrica
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
T2S 160 PR221DS-I In=100A 4p F F	1SDA051182R1	T2S160	Buy on EAN