



Automatización Eléctrica Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

T5D 400 3p F F



General Information Extended Product Type: T5D 400 3p F F Product ID: 1SDA054599R1 EAN: 8015644556976 Catalog Description: T5D 400 3p F F Long Description: SWITCH-DISCONNECTOR TMAX T5D 400 FIXED THREE-POLE WITH FRONT TERMINALS

Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Moulded Case Circuit Breakers » Tmax T

Ordering

EAN:	8015644556976
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

Dimensions

Product Net Width:	140 mm
Product Net Height:	205 mm
Product Net Depth:	103.5 mm
Product Net Weight:	3.25 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	248 mm
Package Level 1 Height:	240 mm
Package Level 1 Length:	285 mm
Package Level 1 Gross Weight:	3.8 kg
Package Level 1 EAN:	8015644556976

Environmental

Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-07-01

Additional Information

IIT Publishing Status:	Level 0 - Information enabled
Mechanical Durability:	20000 cycle 120 cycles per hour
Number of Poles:	3
Power Loss:	at Rated Operating Conditions per Pole 16,5 W
Product Main Type:	SACE Tmax T
Product Name:	Switch-disconnector
Product Type:	SD
Rated Impulse Withstand Voltage (U _{imp}):	8 kV
Rated Insulation Voltage (Ui):	1000 V
Rated Operational Voltage:	690 V AC 750 V DC
Rated Short-time Withstand Current (I_{cw}) :	t for 1 s 5 A
Rated Uninterrupted Current (Iu):	400 A
Standards:	IEC 60947
Sub-type:	Т5
Suitable For:	Т5
Suitable for Product Class:	Moulded Case Circuit Breakers
Terminal Connection Type:	Fixed Circuit-Breakers Front
Test Voltage at Industrial Frequency for 1 Minute:	y 3000 ∨
Test Voltage Max (U _{test}):	3000 V
Version:	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SDC210004D0203			
Declaration of Conformity - CE:	1SDL000165R0005			
RoHS Information:	1SDL000200R0001			
Classifications				
ETIM 4:	EC000228 - Power circuit-breaker for trafo/generator/installation prot.			
ETIM 5:	EC000228 - Power circuit-breaker for trafo/generator/installation prot.			
Object Classification Code:	Q			
UNSPSC:	39121100			





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
T5D 400 3p F F	1SDA054599R1	T5D400	Buy on EAN