



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

# T6L630 TMA630-6300 4pFF N100% 1000VAC/DC



#### **General Information**

Extended Product Type: T6L630 TMA630-6300 4pFF N100% 1000VAC/DC

**Product ID:** 1SDA060315R1 **EAN:** 8015644627836

Catalog Description: T6L630 TMA630-6300 4pFF N100% 1000VAC/DC

Long Description: C.BREAKER TMAX T6L 630 1000V AC-DC FIXED FOUR-POLE WITH FRONT TERMINALS

AND THERMOMAGNETIC RELEASE TMA R 630 I3=3150...6300 A FULLY RATED

#### Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Moulded Case Circuit Breakers » Tmax T

### Ordering

 EAN:
 8015644627836

 Minimum Order Quantity:
 1 piece

 Customs Tariff Number:
 85362090

#### **Dimensions**

Product Net Width:280 mmProduct Net Height:268 mmProduct Net Depth:103.5 mmProduct Net Weight:12 kg

#### **Container Information**

Package Level 1 Units: 1 piece
Package Level 1 Width: 305 mm
Package Level 1 Height: 285 mm
Package Level 1 Length: 370 mm
Package Level 1 Gross Weight: 14 kg
Package Level 1 EAN: 8015644627836

## **Additional Information**

Electrical Durability: 7000 cycle

60 cycles per hour

Mechanical Durability: 20000 cycle
120 cycles per hour

Number of Poles: 4

Power Loss: at Rated Operating Conditions per Pole 30,6 W

Product Main Type: SACE Tmax T

Product Name: Automatic Circuit Breaker

Product Type: CB
Rated Current (In): 630 A
Rated Impulse Withstand Voltage 8 kV

(U<sub>imp</sub>):

Rated Insulation Voltage (U<sub>i</sub>): 1000 V
Rated Operational Voltage: 1000 V AC 1000 V DC

Rated Short-time Withstand Current for 1 s 7,6 A

(I<sub>cw</sub>):

Rated Ultimate Short-Circuit (1000 V AC) 12 kA Breaking Capacity (I<sub>CU</sub>): (1000 V DC) 40 kA

Rated Uninterrupted Current (I<sub>u</sub>): 630 A

Release Type: TM

Standards: IEC 60947

Sub-type: T6

Suitable For: T6

Suitable for Product Class: Moulded Case Circuit Breakers

**Terminal Connection Type:** Fixed Circuit-Breakers

Front

Test Voltage Max (U<sub>test</sub>): 3500 V

Version:	F

# **Certificates and Declarations (Document Number)**

Data Sheet, Technical Information: 1SDC210015D0201

Declaration of Conformity - CE: 1SDL000165R0006

# Classifications

ETIM 4: EC000228 - Power circuit-breaker for trafo/generator/installation prot.

ETIM 5: EC000228 - Power circuit-breaker for trafo/generator/installation prot.

Object Classification Code: Q

**UNSPSC**: 39121100







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
T6L630 TMA630-6300 4pFF N100% 1000VAC/DC	1SDA060315R1	T6L630 1000V	Buy on EAN