



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	T7S 1600 PR332/P LSIRc In=1600A 3p F F M
Product ID:	1SDA063016R1
EAN:	8015644655655
Catalog Description:	T7S 1600 PR332/P LSIRc In=1600A 3p F F M
Long Description:	C.BREAKER TMAX T7S 1600 FIXED THREE-POLE WITH FRONT TERMINALS AND STORED ENERGY OPERATING MECHANISM AND SOLID-STATE RELEASE IN AC PR332/P-LSIRc R 1600

Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Moulded Case Circuit Breakers » Tmax T

Ordering

EAN:	8015644655655
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

Dimensions

Product Net Width:	210 mm
Product Net Height:	268 mm
Product Net Depth:	178 mm
Product Net Weight:	11 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	280 mm
Package Level 1 Height:	350 mm
Package Level 1 Length:	360 mm
Package Level 1 Gross Weight:	12.5 kg
Package Level 1 EAN:	8015644655655

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q2
--------------	---

Additional Information

Number of Poles:	3
Power Loss:	at Rated Operating Conditions per Pole 77 W
Product Main Type:	SACE Tmax T
Product Name:	Automatic Circuit Breaker
Product Type:	CB
Rated Current (I_n):	1600 A
Rated Operational Voltage:	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current (I_{cw}):	for 1 s 20 A
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 8.5 kA (230 V AC) 8.5 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I_u):	1600 A
Release Type:	EL
Standards:	IEC 60947
Sub-type:	T7

Suitable For:	T7M
Suitable for Product Class:	Moulded Case Circuit Breakers
Terminal Connection Type:	Fixed Circuit-Breakers Front
Version:	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SDC210015D0201
Declaration of Conformity - CE:	1SDL000165R0007
GL Certificate:	1SDL000163R0055
RoHS Information:	1SDL000201R0001

Classifications

ETIM 4:	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5:	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
Object Classification Code:	Q
UNSPSC:	39120000





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
T7S 1600 PR332/P LSIRc In=1600A 3p F F M	1SDA063016R1	T7S1600 M	Buy on EAN