



## Automatización Eléctrica Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

## T4V250 PR222DS/P-LSI In100 4p FFC1150VAC



## **General Information**

General Information			
Extended Product Type:	T4V250 PR222DS/P-LSI In100 4p FFC1150VAC		
Product ID:	1SDA063428R1		
EAN:	8015644660529		
Catalog Description:	T4V250 PR222DS/P-LSI In100 4p FFC1150VAC		
Long Description:	C.BREAKER TMAX T4V 250 1150V AC FIXED FOUR-POLE WITH FRONT TERMINALS FOR CABLE Cu AND SOLID-STATE RELEASE IN AC PR222DS/P-LSI R 100		
Categories			
	d Systems » Circuit Breakers » Moulded Case Circuit Breakers » Tmax T		
Troducts // Low Voltage Froducts a	N Systems " Circuit Dieakers " Woulded Case Circuit Dieakers " Imax I		
Ordering			
EAN:	8015644660529		
Minimum Order Quantity:	1 piece		
Customs Tariff Number:	85362090		
	0002000		
Dimensions			
Product Net Width:	105 mm		
Product Net Height:	205 mm		
Product Net Depth:	205 mm		
Product Net Depth: Product Net Weight:			
Froductivet Weight:	3.05 kg		
Container Information			
Package Level 1 Units:	1 piece		
Package Level 1 EAN:	8015644660529		
Package Level 1 EAN:	8013044000329		
Additional Information			
Electrical Durability:	8000 cycle		
Electrical Durability:	120 cycles per hour		
Mechanical Durability:	20000 cycle		
niconanical balability.	240 cycles per hour		
Number of Poles:	4		
Power Loss:	at Rated Operating Conditions per Pole 1,7 W		
Product Main Type:	SACE Tmax T		
Product Name:	Automatic Circuit Breaker		
Product Type:	СВ		
Rated Current (In):	100 A		
Rated Impulse Withstand Voltage	8 kV		
(U <sub>imp</sub> ):			
Rated Insulation Voltage (Ui):	1150 V		
Rated Operational Voltage:	1150 V AC 1000 V DC		
Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> ):	(1000 V AC) 12 kA (1150 V AC) 6 kA		
Rated Ultimate Short-Circuit Breaking Capacity (I <sub>cu</sub> ):	(1000 V AC) 20 kA (1150 V AC) 12 kA		
Rated Uninterrupted Current (I <sub>u</sub> ):	250 A		
Release Type:	EL		
Standards:	IEC 60947		
Sub-type:	T4		
Terminal Connection Type:	Fixed Circuit-Breakers		
isinina connection Type.	Front for Copper Cables		
Test Voltage Max (U <sub>test</sub> ):	3500 V		
Version:	F		
Certificates and Declarations (D	ocument Number)		
Data Sheet, Technical Information:			
Declaration of Conformity - CE:	1SDL000165R0004		
GL Certificate:	1SDL000163R0061		
Classifications			

ETIM 4:EC000228 - Power circuit-breaker for trafo/generator/installation prot.ETIM 5:EC000228 - Power circuit-breaker for trafo/generator/installation prot.Object Classification Code:QUNSPSC:39121100







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
T4V250 PR222DS/P-LSI In100 4p FFC1150VAC	1SDA063428R1	T4V250 1000V	Buy on EAN