



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

# T5L400 PR221DS-LS/I In320 4p FFC 1000VAC



## General Information

Extended Product Type:	T5L400 PR221DS-LS/I In320 4p FFC 1000VAC
Product ID:	1SDA063481R1
EAN:	8015644661137
Catalog Description:	T5L400 PR221DS-LS/I In320 4p FFC 1000VAC
Long Description:	C.BREAKER TMAX T5L 400 1000V AC FIXED FOUR-POLE WITH FRONT TERMINALS FOR CABLE Cu AND SOLID-STATE RELEASE IN AC PR221DS-LS/I R 320

## Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Moulded Case Circuit Breakers » Tmax T

## Ordering

EAN:	8015644661137
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

## Dimensions

Product Net Width:	140 mm
Product Net Height:	205 mm
Product Net Depth:	103.5 mm
Product Net Weight:	4.15 kg

## Container Information

Package Level 1 Units:	1 piece
Package Level 1 EAN:	8015644661137

## Additional Information

Electrical Durability:	7000 cycle 60 cycles per hour
Mechanical Durability:	20000 cycle 120 cycles per hour
Number of Poles:	4
Power Loss:	at Rated Operating Conditions per Pole 10,6 W
Product Main Type:	SACE Tmax T
Product Name:	Automatic Circuit Breaker
Product Type:	CB
Rated Current ( $I_n$ ):	320 A
Rated Impulse Withstand Voltage ( $U_{imp}$ ):	8 kV
Rated Insulation Voltage ( $U_i$ ):	1000 V
Rated Operational Voltage:	1000 V AC 1000 V DC
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ ):	(1000 V AC) 10 kA
Rated Short-time Withstand Current ( $I_{cw}$ ):	for 1 s 5 A
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ):	(1000 V AC) 12 kA
Rated Uninterrupted Current ( $I_u$ ):	400 A
Release Type:	EL
Standards:	IEC 60947
Sub-type:	T5
Terminal Connection Type:	Fixed Circuit-Breakers Front for Copper Cables
Test Voltage Max ( $U_{test}$ ):	3500 V
Version:	F

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SDC210023D0201
Declaration of Conformity - CE:	1SDL000165R0005

## Classifications

---

**ETIM 4:** EC000228 - Power circuit-breaker for trafo/generator/installation prot.

**ETIM 5:** EC000228 - Power circuit-breaker for trafo/generator/installation prot.

**Object Classification Code:** Q

**UNSPSC:** 39121100

---





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

<b>Product</b>	<b>Code</b>	<b>Reference</b>	<b>Product link</b>
T5L400 PR221DS-LS/I In320 4p FFC 1000VAC	1SDA063481R1	T5L400 1000V	<a href="#">Buy on EAN</a>