



Automatización Eléctrica Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

XT4 W FP 4p HR



General Information

Extended Product Type:	XT4 W FP 4p HR
Product ID:	1SDA068207R1
EAN:	8015644021030
Catalog Description:	XT4 W FP 4p HR
Long Description:	FIXED PART WITHDRAWABLE FOR C.BREAKER TMAX FOUR-POLE WITH REAR TERMINALS HORIZONTAL XT4

Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Moulded Case Circuit Breakers » Tmax XT

Ordering

EAN:	8015644021030
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85389099

Dimensions

Product Net Width:	140 mm
Product Net Height:	160 mm
Product Net Depth:	82.5 mm
Product Net Weight:	6.76 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Gross Weight:	2.43 kg
Package Level 1 EAN:	8015644021030

Additional Information

Number of Poles:4Product Main Type:SACE Tmax XTProduct Name:Fixed PartProduct Type:FPRated Frequency (f):50 / 60 HzRated Impulse Withstand Voltage (U _{imp}):8 kVRated Insulation Voltage (U _i):1000 VRated Operational Voltage:690 V AC 500 V DCStandards:IEC 60947Sub-type:XT4Terminal Connection Type:Withdrawable Circuit-Breakers Rear flat HorizontalVersion:W		
Product Name:Fixed PartProduct Type:FPRated Frequency (f):50 / 60 HzRated Impulse Withstand Voltage (U _{imp}):8 kVRated Insulation Voltage (U):1000 VRated Operational Voltage:690 V AC 500 V DCStandards:IEC 60947Sub-type:XT4Terminal Connection Type:Withdrawable Circuit-Breakers Rear flat Horizontal	Number of Poles:	4
Product Type:FPRated Frequency (f):50 / 60 HzRated Impulse Withstand Voltage (U _{imp}):8 kVRated Insulation Voltage (U):1000 VRated Operational Voltage:690 V AC 500 V DCStandards:IEC 60947Sub-type:XT4Terminal Connection Type:Withdrawable Circuit-Breakers Rear flat Horizontal	Product Main Type:	SACE Tmax XT
Rated Frequency (f):50 / 60 HzRated Impulse Withstand Voltage (U _{imp}):8 kVRated Insulation Voltage (U _i):1000 VRated Operational Voltage:690 V AC 500 V DCStandards:IEC 60947Sub-type:XT4Terminal Connection Type:Withdrawable Circuit-Breakers Rear flat Horizontal	Product Name:	Fixed Part
Rated Impulse Withstand Voltage (U _{imp}):8 kVRated Insulation Voltage (U _i):1000 VRated Operational Voltage:690 ∨ AC 500 ∨ DCStandards:IEC 60947Sub-type:XT4Terminal Connection Type:Withdrawable Circuit-Breakers Rear flat Horizontal	Product Type:	FP
(Uimp): IOO ∨ Rated Insulation Voltage (Ui): 1000 ∨ Rated Operational Voltage: 690 ∨ AC 500 ∨ DC 500 ∨ DC Standards: IEC 60947 Sub-type: XT4 Terminal Connection Type: Withdrawable Circuit-Breakers Rear flat Horizontal	Rated Frequency (f):	50 / 60 Hz
Rated Operational Voltage: 690 V AC 500 V DC Standards: IEC 60947 Sub-type: XT4 Terminal Connection Type: Withdrawable Circuit-Breakers Rear flat Horizontal		8 kV
500 V DC Standards: IEC 60947 Sub-type: XT4 Terminal Connection Type: Withdrawable Circuit-Breakers Rear flat Horizontal	Rated Insulation Voltage (Ui):	1000 V
Sub-type: XT4 Terminal Connection Type: Withdrawable Circuit-Breakers Rear flat Horizontal	Rated Operational Voltage:	
Terminal Connection Type: Withdrawable Circuit-Breakers Rear flat Horizontal	Standards:	IEC 60947
Rear flat Horizontal	Sub-type:	XT4
Version: W	Terminal Connection Type:	
	Version:	W

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SDC210033D0202
Declaration of Conformity - CE:	1SDL000165R0009

Classifications

elacomeatione	
Object Classification Code:	Q
UNSPSC:	39120000







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
XT4 W FP 4p HR	1SDA068207R1	XT4	Buy on EAN