



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

## General Information

Extended Product Type:	PSS44/76-500L
Product ID:	1SFA892004R1002
EAN:	7320500206607
Catalog Description:	PSS44/76-500L SOFTSTARTER
Long Description:	Softstarter PSS44/76-500L for max 500V main voltage and 220 - 240V 50/60Hz control supply voltage having a NO fault contact

## Categories

Products » Low Voltage Products and Systems » Control Products » Softstarters » Softstarters

## Ordering

EAN:	7320500206607
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85371099

## Dimensions

Product Net Width:	120.000 mm
Product Net Height:	200.000 mm
Product Net Depth:	162.000 mm
Product Net Weight:	3.2 kg

## Container Information

Package Level 1 Width:	175 mm
Package Level 1 Length:	320 mm
Package Level 1 Height:	235 mm
Package Level 1 Gross Weight:	3 kg
Package Level 1 EAN:	7320500206607
Package Level 1 Units:	1 piece
Package Level 2 Units:	1 piece

## Technical

Rated Operational Voltage:	Main Circuit 208 ... 500 V AC
Rated Control Supply Voltage ( $U_s$ ):	220 ... 240 V AC
Rated Control Circuit Voltage ( $U_c$ ):	DC Operation 24 V
Rated Frequency (f):	Control Supply 50/60 Hz Main Circuit 50/60 Hz
Rated Operational Power - In-Line Connection ( $P_e$ ):	at 500 V 25 kW at 400 V 22 kW at 230 V 11 kW
Rated Operational Current - In-Line Connection ( $I_e$ ):	44 A
Rated Operational Power - Inside Delta Connection:	at 500 V 45 kW at 400 V 37 kW at 230 V 22 kW
Rated Operational Current - Inside Delta Connection:	76 A
Service Factor Percentage:	115 %
Overload Protection:	Recommended TA75DU 18 ... 44
Integrated Electronic Overload:	No
Adjustable Rated Motor Current $I_e$ :	No %
Starting Capacity at Maximum Rated Current $I_e$ :	4x $I_e$ for 10s
Ramp Time:	During Stop 0 ... 30 second(s) During Start 1 ... 30 second(s)
Initial Voltage During Start:	30 ... 70 %
Step Down Voltage Special Ramp:	No %
Current Limit Function:	1.5 ... 4 x $I_e$ if current transformer is connected
Switch for Inside Delta Connection:	Yes
Run Signal Relay:	No
By-pass Signal Relay:	Yes
Fault Signal Relay:	Yes, NO contact
Overload Signal Relay:	No

Signal indication completed start ramp (LED):	Green
Signal indication ready to start/standby ON (LED):	Green
Signal indication running R (LED):	Green
Signal indication fault (LED):	Red
Number of Starts Per Hour at 3.5*Ie for 7 sec. 50% ON Time 50% OFF Time:	30
Communication:	No
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Terminal Type:	Screw Terminals
Connecting Capacity-Main Circuit:	Rigid 1/2x2.5 ... 16 mm²
Connecting Capacity-Control Circuit:	Rigid 2.5 mm²
Connecting Capacity-Supply Circuit:	Rigid 2.5 mm²
Tightening Torque:	Control Circuit 0.5 N·m Supply Circuit 0.5 N·m Main Circuit 2.6 N·m
Product Main Type:	PSS44/76

#### Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	1SFA1-47
RoHS Information:	1SFC132034D0202

#### Environmental

Ambient Air Temperature:	Storage -40 ... +70 °C Operation -25 ... +60 °C
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

#### Classifications

E-nummer:	3302131
UNSPSC:	39121521





**Automatización Eléctrica**  
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
PSS44/76-500L SOFTSTARTER	1SFA892004R1002	PSS44/76-500L	<a href="#">Buy on EAN</a>