



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

| | |
|------------------------|--|
| Extended Product Type: | PSTB570-600-70T |
| Product ID: | 1SFA894017R7020 |
| EAN: | 7320500359372 |
| Catalog Description: | PSTB570-600-70T SOFTSTARTER |
| Long Description: | Softstarter PSTB570-600-70T for max 600V main voltage and 110 - 240V 50/60Hz control supply voltage with coated PCBA |

Categories

Products » Low Voltage Products and Systems » Control Products » Softstarters » Softstarters

Ordering

| | |
|-------------------------|---------------|
| EAN: | 7320500359372 |
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85371099 |

Dimensions

| | |
|---------------------|------------|
| Product Net Width: | 436.000 mm |
| Product Net Height: | 515.000 mm |
| Product Net Depth: | 381.000 mm |
| Product Net Weight: | 52 kg |

Container Information

| | |
|-------------------------------|---------------|
| Package Level 1 Width: | 500 mm |
| Package Level 1 Length: | 600 mm |
| Package Level 1 Height: | 460 mm |
| Package Level 1 Gross Weight: | 64 kg |
| Package Level 1 EAN: | 7320500359372 |
| Package Level 1 Units: | 1 piece |
| Package Level 2 Units: | 1 piece |

Technical

| | |
|---|--|
| Rated Operational Voltage: | Main Circuit 208 ... 600 V AC |
| Rated Control Supply Voltage (U_s): | 100 ... 250 V AC |
| Rated Control Circuit Voltage (U_c): | DC Operation 24 V |
| Rated Frequency (f): | Main Circuit 50/60 Hz Control Supply 50/60 Hz |
| Rated Operational Power - In-Line Connection (P_e): | at 400 V 315 kW at 500 V 400 kW |
| Rated Operational Current - In-Line Connection (I_e): | 570 A |
| Rated Operational Power - Inside Delta Connection: | at 400 V 540 kW at 500 V 700 kW |
| Rated Operational Current - Inside Delta Connection: | 987 A |
| Service Factor Percentage: | 115 % |
| Overload Protection: | Build-in electronic overload protection |
| Integrated Electronic Overload: | Yes |
| Adjustable Rated Motor Current I_e : | 30 ... 115 % |
| Starting Capacity at Maximum Rated Current I_e : | 3xle for 15s |
| Ramp Time: | During Start 1 ... 30 second(s) During Start 1 ... 120 second(s) During Stop 0 ... 30 second(s) During Stop 0 ... 120 second(s) |
| Initial Voltage During Start: | 30 ... 70 % |
| Step Down Voltage Special Ramp: | 100...30 % |
| Current Limit Function: | 1.5 ... 7xle |
| Switch for Inside Delta Connection: | Yes |
| Run Signal Relay: | Yes |
| By-pass Signal Relay: | Yes |
| Fault Signal Relay: | Yes |
| Overload Signal Relay: | Yes |

| | |
|--|--|
| Analog Outputs: | 0...10 volts 0...20 mA 4...20 mA |
| Signal indication ready to start/standby ON (LED): | Green |
| Signal indication protection (LED): | Yellow |
| Signal indication fault (LED): | Red |
| Number of Starts Per Hour at 3.5*I_e for 7 sec. 50% ON Time 50% OFF Time: | 10 |
| Communication: | FiledBusPlug(Standard) |
| Degree of Protection: | acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00 |
| Terminal Type: | Main Circuit: Bars |
| Connecting Capacity-Main Circuit: | Hole Diameter 12.5 mm Width and Thickness 40x6 mm |
| Connecting Capacity-Control Circuit: | Rigid 1x2.5 mm ² Rigid 2x1.5 mm ² |
| Connecting Capacity-Supply Circuit: | Rigid 1x2.5 mm ² Rigid 2x1.5 mm ² |
| Tightening Torque: | Main Circuit 45 N·m Supply Circuit 0.5 N·m Control Circuit 0.5 N·m |
| Product Main Type: | PSTB570 |

Certificates and Declarations (Document Number)

| | |
|--|-----------------|
| Declaration of Conformity - CE: | 1SFA1-76 |
| RoHS Information: | 1SFC132035D0201 |

Environmental

| | |
|---------------------------------|---|
| Ambient Air Temperature: | Operation 0 ... +50 °C Storage -25 ... +70 °C |
| Battery Information: | Button Cell Yes Contains Cd <0.01 % Contains Hg <0.01 % Contains Pb <0.01 % Type Portable Weight 0.0031 kg |
| RoHS Status: | No declaration needed |





Automatización Eléctrica
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| Product | Code | Reference | Product link |
|-----------------------------|-----------------|-----------------|----------------------------|
| PSTB570-600-70T SOFTSTARTER | 1SFA894017R7020 | PSTB570-600-70T | Buy on EAN |