



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

## General Information

Extended Product Type:	UA95-30-00 220V 50Hz / 220-240V 60Hz
Product ID:	1SFL431022R7600
EAN:	7320500144558
Catalog Description:	UA95-30-00 220V 50Hz / 220-240V 60Hz Contactor
Long Description:	A 3-phase Contactor suitable for Capacitor switching application. Maximum permissible peak current 30 times the nominal RMS current. Operated with a control voltage, versions from 24V to 690 V

## Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Block Contactors

## Ordering

EAN:	7320500144558
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364900

## Dimensions

Product Net Width:	90.0 mm
Product Net Depth:	123.5 mm
Product Net Height:	148.0 mm
Product Net Weight:	2.000 kg

## Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	140 mm
Package Level 1 Length:	140 mm
Package Level 1 Height:	170 mm
Package Level 1 Gross Weight:	2 kg
Package Level 1 EAN:	7320500144558

## Technical

Number of Main Contacts NO:	3
Number of Main Contacts NC:	0
Number of Auxiliary Contacts NO:	0
Number of Auxiliary Contacts NC:	0
Rated Operational Voltage:	Main Circuit 1000 V
Rated Frequency (f):	Main Circuit 50/60 Hz
Conventional Free-air Thermal Current ( $I_{th}$ ):	acc. to IEC 60947-4-1, Open Contactors $q = 40^\circ\text{C}$ 145 A
Rated Short-time Withstand Current ( $I_{cw}$ ):	at $40^\circ\text{C}$ Ambient Temp, in Free Air, from a Cold State 30 s 500 A at $40^\circ\text{C}$ Ambient Temp, in Free Air, from a Cold State 15 min 160 A at $40^\circ\text{C}$ Ambient Temp, in Free Air, from a Cold State 10 s 800 A at $40^\circ\text{C}$ Ambient Temp, in Free Air, from a Cold State 1 s 1320 A at $40^\circ\text{C}$ Ambient Temp, in Free Air, from a Cold State 1 min 350 A
Maximum Breaking Capacity:	$\cos \phi = 0.45$ ( $\cos \phi = 0.35$ for $I_e > 100$ A) at 440 V 1160 A $\cos \phi = 0.45$ ( $\cos \phi = 0.35$ for $I_e > 100$ A) at 690 V 800 A
Maximum Electrical Switching Frequency:	240 cycles per hour
Rated Insulation Voltage ( $U_i$ ):	acc. to UL/CSA 600 V acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V
Rated Impulse Withstand Voltage ( $U_{imp}$ ):	Main Circuit 8 kV
Mechanical Durability:	10 million
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Coil Operating Limits:	(acc. to IEC 60947-4-1) $0.85 \times U_c \text{ Min.} \dots 1.1 \times U_c \text{ Max.}$ (at $\theta \leq 70^\circ\text{C}$ ) $^\circ\text{C}$
Rated Control Circuit Voltage ( $U_c$ ):	60 Hz 220 ... 240 V 50 Hz 220 V
Coil Consumption:	Pull-in at Max. Rated Control Circuit Voltage 60 Hz 450 V·A Holding at Max. Rated Control Circuit Voltage 50 Hz 22 V·A Pull-in at Max. Rated Control Circuit Voltage 50 Hz 350 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 26 V·A
Operate Time:	Between Coil Energization and NO Contact Closing 10 ... 25 ms

	Between Coil De-energization and NC Contact Closing 7 ... 15 ms
<b>Connecting Capacity-Main Circuit:</b>	Flexible with Cable End 2x6...35 mm <sup>2</sup> Bar 30 mm <sup>2</sup> Rigid 2x6...65 mm <sup>2</sup>
<b>Connecting Capacity-Auxiliary Circuit:</b>	Solid 1x1...4 mm <sup>2</sup> Flexible with Insulated Ferrule 2x0.75...2.5 mm <sup>2</sup> Stranded 1x1...4 mm <sup>2</sup> Flexible 2x0.75...2.5 mm <sup>2</sup> Flexible with Ferrule 1x0.75...2.5 mm <sup>2</sup>
<b>Degree of Protection:</b>	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
<b>Connecting terminals (delivered in open position) Main poles:</b>	M8 hexagon socket screw with single connector
<b>Terminal Type:</b>	Cable Clamp

## Environmental

<b>Ambient Air Temperature:</b>	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25...+50 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40...+70 °C Close to Contactor for Storage -60...+80 °C
<b>Maximum Operating Altitude Permissible:</b>	3000 m
<b>Resistance to Shock acc. to IEC 60068-2-27:</b>	Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: A 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: C2 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: B1 15 g Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: A 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: B2 15 g Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: C1 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: C2 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: B1 5 g Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: C1 20 g
<b>RoHS Status:</b>	Following EU Directive 2002/95/EC August 18, 2005 and amendment

## Technical UL/CSA

<b>Maximum Operating Voltage UL/CSA:</b>	Main Circuit 600 V
--	--------------------

## Certificates and Declarations (Document Number)

<b>CB Certificate:</b>	SE-72472
<b>CCC Certificate:</b>	CQC_2003010304088242
<b>Declaration of Conformity - CE:</b>	1SFA1-63
<b>RoHS Information:</b>	1SFC101046D0203

## Classifications

<b>ETIM 5:</b>	EC001079 - Capacitor magnet contactor
<b>UNSPSC:</b>	39121529





**Automatización Eléctrica**  
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
UA95-30-00 220V 50Hz / 220-240V 60Hz Contactor	1SFL431022R7600	UA95-30-00	<a href="#">Buy on EAN</a>