



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

## General Information

Extended Product Type:	AF140-30-11B-13
Product ID:	1SFL447002R1311
EAN:	7320500476963
Catalog Description:	AF140-30-11B-13 Contactor
Long Description:	A 3-phase Contactor suitable for various applications such as Motor starting, Isolation, Bypass and Distribution application up to max 690 V. Operated with wide control voltage range 100-250 V, 50/60 Hz and DC

## Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Block Contactors

## Ordering

EAN:	7320500476963
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364900

## Dimensions

Product Net Width:	90.0 mm
Product Net Depth:	126.0 mm
Product Net Height:	150.0 mm
Product Net Weight:	1.648 kg

## Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	194 mm
Package Level 1 Length:	115 mm
Package Level 1 Height:	169 mm
Package Level 1 Gross Weight:	1.57 kg
Package Level 1 EAN:	7320500476963

## Technical

Number of Main Contacts NO:	3
Number of Main Contacts NC:	0
Number of Auxiliary Contacts NO:	1
Number of Auxiliary Contacts NC:	1
Rated Operational Voltage:	Main Circuit 690 V
Rated Frequency (f):	Main Circuit 50/60 Hz
Conventional Free-air Thermal Current ( $I_{th}$ ):	acc. to IEC 60947-4-1, Open Contactors $q = 40^\circ\text{C}$ 200 A
Rated Operational Current AC-1 ( $I_e$ ):	(690 V) $55^\circ\text{C}$ 175 A (690 V) $40^\circ\text{C}$ 200 A (690 V) $70^\circ\text{C}$ 160 A
Rated Operational Current AC-3 ( $I_e$ ):	(220 / 230 / 240 V) $55^\circ\text{C}$ 140 A (690 V) $55^\circ\text{C}$ 80 A (415 V) $55^\circ\text{C}$ 140 A (440 V) $55^\circ\text{C}$ 140 A (380 / 400 V) $55^\circ\text{C}$ 140 A (500 V) $55^\circ\text{C}$ 130 A
Rated Operational Power AC-3 ( $P_e$ ):	(500 V) 90 kW (690 V) 75 kW (220 / 230 / 240 V) 37 kW (380 / 400 V) 75 kW (440 V) 90 kW (415 V) 75 kW
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1:	8 x $I_e$ AC-3
Rated Making Capacity AC-3 acc. to IEC 60947-4-1:	10 x $I_e$ AC-3
Short-Circuit Protective Devices:	gG Type Fuses 315 A
Rated Short-time Withstand Current ( $I_{cw}$ ):	at $40^\circ\text{C}$ Ambient Temp, in Free Air, from a Cold State 15 min 200 A at $40^\circ\text{C}$ Ambient Temp, in Free Air, from a Cold State 10 s 1168 A at $40^\circ\text{C}$ Ambient Temp, in Free Air, from a Cold State 30 s 674 A at $40^\circ\text{C}$ Ambient Temp, in Free Air, from a Cold State 1 s 1460 A at $40^\circ\text{C}$ Ambient Temp, in Free Air, from a Cold State 1 min 477 A

<b>Maximum Breaking Capacity:</b>	cos phi=0.45 (cos phi=0.35 for I <sub>e</sub> > 100 A) at 440 V 3000 A cos phi=0.45 (cos phi=0.35 for I <sub>e</sub> > 100 A) at 690 V 1500 A
<b>Maximum Electrical Switching Frequency:</b>	AC-3 300 cycles per hour AC-1 300 cycles per hour AC-2 / AC-4 150 cycles per hour
<b>Rated Operational Current DC-1 (I<sub>e</sub>):</b>	(110 V) 2 Poles in Series, 40 °C 160 A (220 V) 3 Poles in Series, 40 °C 160 A
<b>Rated Operational Current DC-3 (I<sub>e</sub>):</b>	(110 V) 2 Poles in Series, 40 °C 160 A (220 V) 3 Poles in Series, 40 °C 160 A
<b>Rated Operational Current DC-5 (I<sub>e</sub>):</b>	(110 V) 2 Poles in Series, 40 °C 160 A (220 V) 3 Poles in Series, 40 °C 160 A
<b>Rated Insulation Voltage (U<sub>i</sub>):</b>	acc. to UL/CSA 600 V acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 690 V
<b>Rated Impulse Withstand Voltage (U<sub>imp</sub>):</b>	Main Circuit 8 kV
<b>Mechanical Durability:</b>	5 million
<b>Maximum Mechanical Switching Frequency:</b>	300 cycles per hour
<b>Coil Operating Limits:</b>	(acc. to IEC 60947-4-1) 0.85 x U <sub>c</sub> Min. ... 1.1 x U <sub>c</sub> Max. (at θ ≤ 70 °C) °C
<b>Rated Control Circuit Voltage (U<sub>c</sub>):</b>	60 Hz 100...250 V 50 Hz 100...250 V DC Operation 100...250 V
<b>Coil Consumption:</b>	Pull-in at Max. Rated Control Circuit Voltage 60 Hz 130 V·A Holding at Max. Rated Control Circuit Voltage DC 3 W Holding at Max. Rated Control Circuit Voltage 50 Hz 6 V·A Pull-in at Max. Rated Control Circuit Voltage DC 135 W Pull-in at Max. Rated Control Circuit Voltage 50 Hz 130 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 6 V·A
<b>Operate Time:</b>	Between Coil Energization and NO Contact Closing 25...55 ms Between Coil De-energization and NO Contact Opening 37...47 ms
<b>Connecting Capacity-Main Circuit:</b>	Rigid Cu-Cable 2x10...95 mm <sup>2</sup> Flexible 2x10...70 mm <sup>2</sup>
<b>Connecting Capacity-Auxiliary Circuit:</b>	Solid 1x1...4 mm <sup>2</sup> Flexible with Insulated Ferrule 2x0.75...2.5 mm <sup>2</sup> Stranded 2x1...4 mm <sup>2</sup> Flexible 2x0.75...2.5 mm <sup>2</sup> Flexible with Ferrule 2x0.75...2.5 mm <sup>2</sup>
<b>Degree of Protection:</b>	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
<b>Terminal Type:</b>	Main Circuit: Bars

## Environmental

<b>Ambient Air Temperature:</b>	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 U <sub>c</sub> ) -25...+50 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 U <sub>c</sub> ) -40...+70 °C Close to Contactor for Storage -40...+70 °C
<b>Maximum Operating Altitude Permissible:</b>	3000 m
<b>RoHS Status:</b>	Following EU Directive 2002/95/EC August 18, 2005 and amendment

## Technical UL/CSA

<b>Maximum Operating Voltage UL/CSA:</b>	Main Circuit 600 V
<b>General Use Rating UL/CSA:</b>	(600 V AC) 200 A
<b>Horsepower Rating UL/CSA:</b>	(208 V AC) Three Phase 40 Hp (440 ... 480 V AC) Three Phase 100 Hp (550 ... 600 V AC) Three Phase 125 Hp (220 ... 240 V AC) Three Phase 50 Hp (200 V AC) Three Phase 40 Hp

## Certificates and Declarations (Document Number)

<b>CB Certificate:</b>	SE-70480
<b>CCC Certificate:</b>	CQC_2013010304604055
<b>Declaration of Conformity - CE:</b>	2CMT004242
<b>RINA Certificate:</b>	ELE060313XG/002
<b>RoHS Information:</b>	1SFC101055D0202

## Classifications

<b>E-nummer:</b>	3210109
<b>ETIM 5:</b>	EC000066 - Magnet contactor, AC-switching
<b>UNSPSC:</b>	39121529





**Automatización Eléctrica**  
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
AF140-30-11B-13 Contactor	1SFL447002R1311	AF140-30-11B-13	<a href="#">Buy on EAN</a>