



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

## General Information

|                               |  |
|-------------------------------|--|
| <b>Extended Product Type:</b> | AF370-30-00-13 100-250V 50/60Hz / DC   |
| <b>Product ID:</b>            | 1SFL607002R1300  |
| <b>EAN:</b>                   | 7320500481882  |
| <b>Catalog Description:</b>   | AF370-30-00-13 Contactor   |
| <b>Long Description:</b>      | A 3-phase Contactor suitable for various applications such as Motor starting, Isolation, Bypass and Distribution application up to max 1000 V. Operated with wide control voltage range 100-250 V, 50/60 Hz and DC |

## Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Block Contactors

## Ordering

|                                |               |
|--------------------------------|---------------|
| <b>EAN:</b>                    | 7320500481882 |
| <b>Minimum Order Quantity:</b> | 1 piece       |
| <b>Customs Tariff Number:</b>  | 85364900      |

## Dimensions

|                            |          |
|----------------------------|----------|
| <b>Product Net Width:</b>  | 140.0 mm |
| <b>Product Net Depth:</b>  | 180.0 mm |
| <b>Product Net Height:</b> | 225.0 mm |
| <b>Product Net Weight:</b> | 4.605 kg |

## Container Information

|                                      |               |
|--------------------------------------|---------------|
| <b>Package Level 1 Units:</b>        | 1 piece       |
| <b>Package Level 1 Width:</b>        | 223 mm        |
| <b>Package Level 1 Length:</b>       | 175 mm        |
| <b>Package Level 1 Height:</b>       | 270 mm        |
| <b>Package Level 1 Gross Weight:</b> | 5.275 kg      |
| <b>Package Level 1 EAN:</b>          | 7320500481882 |

## Technical

|  |  |
|--|--|
| <b>Number of Main Contacts NO:</b>                             | 3  |
| <b>Number of Main Contacts NC:</b>                             | 0  |
| <b>Number of Auxiliary Contacts NO:</b>                        | 0  |
| <b>Number of Auxiliary Contacts NC:</b>                        | 0  |
| <b>Rated Operational Voltage:</b>                              | Main Circuit 1000 V  |
| <b>Rated Frequency (f):</b>                                    | Main Circuit 50/60 Hz  |
| <b>Conventional Free-air Thermal Current (I<sub>th</sub>):</b> | acc. to IEC 60947-4-1, Open Contactors q = 40 °C 600 A   |
| <b>Rated Operational Current AC-1 (I<sub>e</sub>):</b>         | (690 V) 55 °C 500 A<br>(690 V) 40 °C 600 A<br>(1000 V) 40 °C 400 A<br>(1000 V) 55 °C 350 A<br>(690 V) 70 °C 400 A<br>(1000 V) 70 °C 290 A  |
| <b>Rated Operational Current AC-3 (I<sub>e</sub>):</b>         | (1000 V) 55 °C 100 A<br>(415 V) 55 °C 370 A<br>(220 / 230 / 240 V) 55 °C 370 A<br>(690 V) 55 °C 315 A<br>(440 V) 55 °C 370 A<br>(380 / 400 V) 55 °C 370 A<br>(500 V) 55 °C 315 A |
| <b>Rated Operational Power AC-3 (P<sub>e</sub>):</b>           | (500 V) 250 kW<br>(1000 V) 132 kW<br>(220 / 230 / 240 V) 110 kW<br>(690 V) 315 kW<br>(380 / 400 V) 200 kW<br>(440 V) 200 kW<br>(415 V) 200 kW                                    |
| <b>Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1:</b>     | 8 x I <sub>e</sub> AC-3  |
| <b>Rated Making Capacity AC-3 acc. to IEC 60947-4-1:</b>       | 10 x I <sub>e</sub> AC-3   |
| <b>Short-Circuit Protective Devices:</b>                       | gG Type Fuses 630 A  |
| <b>Rated Short-time Withstand Current</b>                      | at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 600 A   |

|   |  |
|---|--|
| <b>(I<sub>cw</sub>):</b>                                  | at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 1709 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 2960 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 3700 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 1208 A   |
| <b>Maximum Breaking Capacity:</b>                         | cos phi=0.45 (cos phi=0.35 for I <sub>e</sub> > 100 A) at 440 V 5000 A<br>cos phi=0.45 (cos phi=0.35 for I <sub>e</sub> > 100 A) at 690 V 4000 A   |
| <b>Maximum Electrical Switching Frequency:</b>            | AC-3 300 cycles per hour<br>AC-1 300 cycles per hour<br>AC-2 / AC-4 150 cycles per hour  |
| <b>Rated Operational Current DC-1 (I<sub>e</sub>):</b>    | (110 V) 2 Poles in Series, 40 °C 450 A<br>(220 V) 3 Poles in Series, 40 °C 450 A   |
| <b>Rated Operational Current DC-3 (I<sub>e</sub>):</b>    | (110 V) 2 Poles in Series, 40 °C 450 A<br>(220 V) 3 Poles in Series, 40 °C 450 A   |
| <b>Rated Operational Current DC-5 (I<sub>e</sub>):</b>    | (110 V) 2 Poles in Series, 40 °C 450 A<br>(220 V) 3 Poles in Series, 40 °C 450 A   |
| <b>Rated Insulation Voltage (U<sub>i</sub>):</b>          | acc. to UL/CSA 600 V<br>acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V  |
| <b>Rated Impulse Withstand Voltage (U<sub>imp</sub>):</b> | Main Circuit 8 kV  |
| <b>Mechanical Durability:</b>                             | 5 million  |
| <b>Maximum Mechanical Switching Frequency:</b>            | 300 cycles per hour  |
| <b>Coil Operating Limits:</b>                             | (acc. to IEC 60947-4-1) 0.85 x U <sub>c</sub> Min. ... 1.1 x U <sub>c</sub> Max. (at θ ≤ 70 °C) °C   |
| <b>Rated Control Circuit Voltage (U<sub>c</sub>):</b>     | 60 Hz 100...250 V<br>50 Hz 100...250 V<br>DC Operation 100...250 V   |
| <b>Coil Consumption:</b>                                  | Pull-in at Max. Rated Control Circuit Voltage 60 Hz 385 V·A<br>Holding at Max. Rated Control Circuit Voltage DC 4.5 W<br>Holding at Max. Rated Control Circuit Voltage 50 Hz 17.5 V·A<br>Pull-in at Max. Rated Control Circuit Voltage DC 410 W<br>Pull-in at Max. Rated Control Circuit Voltage 50 Hz 385 V·A<br>Holding at Max. Rated Control Circuit Voltage 60 Hz 17.5 V·A |
| <b>Operate Time:</b>                                      | Between Coil Energization and NO Contact Closing 25...55 ms<br>Between Coil De-energization and NO Contact Opening 37...47 ms  |
| <b>Connecting Capacity-Main Circuit:</b>                  | Rigid Al-Cable 1x185...240 mm <sup>2</sup><br>Flexible 2x70...185 mm <sup>2</sup><br>Rigid Cu-Cable 1x6...300 mm <sup>2</sup>  |
| <b>Connecting Capacity-Auxiliary Circuit:</b>             | Solid 2x1...4 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x0.75...2.5 mm <sup>2</sup><br>Stranded 2x1...4 mm <sup>2</sup><br>Flexible 2x0.75...2.5 mm <sup>2</sup><br>Flexible with Ferrule 1x0.75...2.5 mm <sup>2</sup>   |
| <b>Degree of Protection:</b>                              | acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20<br>acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00   |
| <b>Terminal Type:</b>                                     | Main Circuit: Bars   |

## Environmental

|  |   |
|--|---|
| <b>Ambient Air Temperature:</b>                | Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 U <sub>c</sub> ) -25...+50 °C<br>Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 U <sub>c</sub> ) -40...+70 °C<br>Close to Contactor for Storage -40...+70 °C |
| <b>Maximum Operating Altitude Permissible:</b> | 3000 m  |
| <b>RoHS Status:</b>                            | Following EU Directive 2002/95/EC August 18, 2005 and amendment   |

## Technical UL/CSA

|  |   |
|--|---|
| <b>Maximum Operating Voltage UL/CSA:</b> | Main Circuit 600 V  |
| <b>General Use Rating UL/CSA:</b>        | (600 V AC) 520 A  |
| <b>Horsepower Rating UL/CSA:</b>         | (208 V AC) Three Phase 125 Hp<br>(440 ... 480 V AC) Three Phase 300 Hp<br>(550 ... 600 V AC) Three Phase 350 Hp<br>(220 ... 240 V AC) Three Phase 150 Hp<br>(200 V AC) Three Phase 125 Hp |

## Certificates and Declarations (Document Number)

|  |                 |
|--|-----------------|
| <b>CB Certificate:</b>                 | SE-73044M1      |
| <b>Declaration of Conformity - CE:</b> | 2CMT004749      |
| <b>RINA Certificate:</b>               | ELE060313XG/002 |
| <b>RoHS Information:</b>               | 1SFC101055D0202 |

## Classifications

|                  |         |
|------------------|---------|
| <b>E-nummer:</b> | 3210167 |
|------------------|---------|

**ETIM 5:** EC000066 - Magnet contactor, AC-switching  
**UNSPSC:** 39121529

---





**Automatización Eléctrica**  
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| <b>Product</b>           | <b>Code</b>     | <b>Reference</b> | <b>Product link</b>        |
|--------------------------|-----------------|------------------|----------------------------|
| AF370-30-00-13 Contactor | 1SFL607002R1300 | AF370-30-00-13   | <a href="#">Buy on EAN</a> |