



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

AF2650-30-11 100-250V 50/60Hz / 100-250 DC



General Information

Extended Product Type:	AF2650-30-11 100-250V 50/60Hz / 100-250 DC
Product ID:	1SFL667001R7011
EAN:	7320500481431
Catalog Description:	AF2650-30-11 100-250V 50/60Hz / 100-250 DC Contactor
Long Description:	A 3-phase Contactor suitable for various applications such as Isolation, By-pass and Distribution application up to max 1000 V. Operated with wide control voltage range 100-250 V, AC/DC

Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Block Contactors

Ordering

EAN:	7320500481431
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364900

Dimensions

Product Net Width:	438.0 mm
Product Net Depth:	244.0 mm
Product Net Height:	422.0 mm
Product Net Weight:	41.000 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	250 mm
Package Level 1 Length:	440 mm
Package Level 1 Height:	430 mm
Package Level 1 Gross Weight:	43 kg
Package Level 1 EAN:	7320500481431

Technical

Number of Main Contacts NO:	3
Number of Main Contacts NC:	0
Number of Auxiliary Contacts NO:	1
Number of Auxiliary Contacts NC:	1
Rated Operational Voltage:	Main Circuit 1000 V
Rated Frequency (f):	Main Circuit 50/60 Hz
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-4-1, Open Contactors $q = 40^\circ\text{C}$ 2650 A
Rated Operational Current AC-1 (I_e):	(690 V) 55°C 2350 A (690 V) 40°C 2650 A (1000 V) 40°C 2650 A (1000 V) 55°C 2350 A (690 V) 70°C 2120 A (1000 V) 70°C 2120 A
Rated Making Capacity AC-3 acc. to IEC 60947-4-1:	10 x I_e AC-3
Rated Short-time Withstand Current (I_{cw}):	at 40°C Ambient Temp, in Free Air, from a Cold State 30 s 7500 A at 40°C Ambient Temp, in Free Air, from a Cold State 10 s 10000 A at 40°C Ambient Temp, in Free Air, from a Cold State 15 min 2200 A at 40°C Ambient Temp, in Free Air, from a Cold State 1 s 12000 A at 40°C Ambient Temp, in Free Air, from a Cold State 1 min 5500 A
Maximum Breaking Capacity:	$\cos \phi = 0.45$ ($\cos \phi = 0.35$ for $I_e > 100$ A) at 440 V 8400 A
Maximum Electrical Switching Frequency:	AC-1 15 cycles per hour
Rated Insulation Voltage (U_i):	acc. to UL/CSA 1000 V acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V
Rated Impulse Withstand Voltage (U_{imp}):	Main Circuit 8 kV
Mechanical Durability:	0.3 million
Maximum Mechanical Switching Frequency:	300 cycles per hour
Coil Operating Limits:	(acc. to IEC 60947-4-1) $0.85 \times U_c$ Min. ... $1.1 \times U_c$ Max. (at $\theta \leq 70^\circ\text{C}$) $^\circ\text{C}$

Rated Control Circuit Voltage (U_c):	60 Hz 100...250 V 50 Hz 100...250 V DC Operation 100...250 V
Coil Consumption:	Pull-in at Max. Rated Control Circuit Voltage 60 Hz 2450 V·A Holding at Max. Rated Control Circuit Voltage DC 20.5 V·A Holding at Max. Rated Control Circuit Voltage 50 Hz 48 V·A Pull-in at Max. Rated Control Circuit Voltage DC 2290 V·A Pull-in at Max. Rated Control Circuit Voltage 50 Hz 2450 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 48 V·A
Operate Time:	Between Coil Energization and NO Contact Closing 50...80 ms Between Coil De-energization and NO Contact Opening 35...55 ms Between Coil De-energization and NC Contact Closing 35...55 ms Between Coil Energization and NC Contact Opening 50...80 ms
Connecting Capacity-Main Circuit:	Bar 100 mm
Connecting Capacity-Auxiliary Circuit:	Solid 2x1...4 mm ² Flexible with Insulated Ferrule 2x0.75...2.5 mm ² Stranded 2x1...4 mm ² Flexible 2x0.75...2.5 mm ² Flexible with Ferrule 2x0.75...2.5 mm ²
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
Terminal Type:	Main Circuit: Bars

Environmental

Ambient Air Temperature:	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 U _c) -25...+50 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 U _c) -40...+70 °C Close to Contactor for Storage -40...+70 °C
Maximum Operating Altitude Permissible:	3000 m

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
General Use Rating UL/CSA:	(600 V AC) 2700 A

Certificates and Declarations (Document Number)

CB Certificate:	SE-70500M1
CCC Certificate:	CQC_2013010304604054
Declaration of Conformity - CE:	2CMT004707
RINA Certificate:	ELE060313XG/002
RoHS Information:	1SFC101061D0201

Classifications

ETIM 5:	EC000066 - Magnet contactor, AC-switching
UNSPSC:	39121529





Automatización Eléctrica
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
AF2650-30-11 100-250V 50/60Hz / 100-250 DC Contactor	1SFL667001R7011	AF2650-30-11	Buy on EAN