



Automatización Eléctrica Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

RB121A-24VAC/DC



General Information Extended Product Type: RB121A-24VAC/DC Product ID: 1SNA645005R0700 EAN: 4013614507762 Catalog Description: RB121A-24VAC/DC Interface relay R600 1c/o,A1-A2=24VAC/DC,250V/1mA-6A,LED Long Description: Screw relay RB121A 24vac/dc : 24vac-dc input / 1SPDT 1 mA upto 6A with led

Categories

Products » Low Voltage Products and Systems » Control Products » Electronic Relays and Controls » Interface Relays and Optocouplers

Environage 4013614507762 Minimum Order Quantify: 10 piece Customs Tariff Number: 85364900 Dimensions	Ordering	
Minimum Order Quantity: 10 piece Customs Tariff Number: 85364900 Dimensions	v	4013614507762
Customs Tariff Number: 85364900 Dimensions Froduct Net Width: 6 mm Product Net Height: 67.5 mm Product Net Depth: 70 mm Product Net Weight: 0.02 kg Container Information Product Net Weight: 0.02 kg Container Information Package Level 1 Width: 73 mm Package Level 1 Width: 73 mm Package Level 1 Width: 73 mm Package Level 1 Length: 80 mm Package Level 1 Length: 80 mm Package Level 1 Length: 80 mm Package Level 1 EAN: 3472596450052 Package Level 1 EAN: 3472596450052 Technical Event 1 EAN: 3472596450052 Package Level 1 EAN: 3472596450052 Technical Event 1 EAN: 3472596450052 Package Level 1 EAN: 3472596450052 Technical Event 1 EAN: 3472596450052 Package Level 1 EAN: 3472596450052 Technical Event 1 EAN: 3472596450052 Package Level 1 EAN: 3472596450052 Cottomicin: Boxed Interface relay R600 Sub-Function: Soved Interface relay R600 Sub-Function: Soved Interface relay R600 Sub-Function: Soved C/1 nh 6 A Rated Cont		
Dimensions Product Net Wildth: 6 mm Product Net Height: 67.5 mm Product Net Depth: 70 mm Product Net Weight: 0.02 kg Container Information		•
Product Net Width: 6 mm Product Net Height: 67.5 mm Product Net Depth: 70 mm Product Net Weight: 0.02 kg Container Information		
Product Net Height: 67.5 mm Product Net Depth: 70 mm Product Net Weight: 0.02 kg Container Information	Dimensions	
Product Net Depth: 70 mm Product Net Weight: 0.02 kg Container Information	Product Net Width:	6 mm
Product Net Weight: 0.02 kg Container Information	Product Net Height:	67.5 mm
Container Information Package Level 1 Units: 10 piece Package Level 1 Width: 73 mm Package Level 1 Height: 71 mm Package Level 1 Length: 80 mm Package Level 1 Gross Weight: 0.23 kg Package Level 1 EAN: 3472596450052 Technical Function: Function: Boxed interface relay R600 Sub-Function: Relay with built in LED Output: 1 c/o (SPDT) contact Output Signal: 5 250 V AC / 1 mA 6 A Rated Control Supply Voltage (Us): 24 V AC/DC Terminal Type: Screw Terminals Certificate: CSA_254821 cuR Certificate: cuR_252056 Declaration of Conformity - CE: 1SND2250422(1000 EAC Certificate: LRS_0520042 UR Certificate: LRS_0520042 UR Certificate: LRS_0520042 UR Certifica	Product Net Depth:	70 mm
Package Level 1 Units: 10 piece Package Level 1 Height: 73 mm Package Level 1 Height: 71 mm Package Level 1 Length: 80 mm Package Level 1 Gross Weight: 0.23 kg Package Level 1 EAN: 3472596450052 Technical	Product Net Weight:	0.02 kg
Package Level 1 Width:73 mmPackage Level 1 Height:71 mmPackage Level 1 Length:80 mmPackage Level 1 Gross Weight:0.23 kgPackage Level 1 Gross Weight:0.23 kgPackage Level 1 Gross Weight:0.23 kgPackage Level 1 EAN:3472596450052TechnicalFunction:Boxed interface relay R600Sub-Function:Relay with built in LEDOutput:1 c/o (SPDT) contactOutput:5 250 V AC / 1 mA 6 ARated Control Supply Voltage (Us):24 V AC/DCTerminal Type:Screw TerminalsCertificates and Declarations (Document Number)CSA Certificate:cSA_254821cUR Certificate:cUR_E352056Declaration of Conformity - CE:1 SIND25042C1000EAC Certificate:LRS_0620042UR Certificate:UR_E352056ClassificationsOutput2Object Classification Code:KETIM 4:EC001437 - Switching relayETIM 5:EC001437 - Switching relay	Container Information	
Package Level 1 Width:73 mmPackage Level 1 Height:71 mmPackage Level 1 Length:80 mmPackage Level 1 Gross Weight:0.23 kgPackage Level 1 Gross Weight:0.23 kgPackage Level 1 Gross Weight:0.23 kgPackage Level 1 EAN:3472596450052TechnicalFunction:Boxed interface relay R600Sub-Function:Relay with built in LEDOutput:1 c/o (SPDT) contactOutput:5 250 V AC / 1 mA 6 ARated Control Supply Voltage (Us):24 V AC/DCTerminal Type:Screw TerminalsCertificates and Declarations (Document Number)CSA Certificate:cSA_254821cUR Certificate:cUR_E352056Declaration of Conformity - CE:1 SIND25042C1000EAC Certificate:LRS_0620042UR Certificate:UR_E352056ClassificationsOutput2Object Classification Code:KETIM 4:EC001437 - Switching relayETIM 5:EC001437 - Switching relay	Package Level 1 Units:	10 piece
Package Level 1 Length:80 mmPackage Level 1 Gross Weight:0.23 kgPackage Level 1 EAN:3472596450052TechnicalFunction:Boxed interface relay R600Sub-Function:Relay with built in LEDOutput:1 c/o (SPDT) contactOutput Signal:5 250 V AC / 1 mA 6 ARated Control Supply Voltage (Us):24 V AC/DCTerminal Type:Screw TerminalsCertificates and Declarations (Document Number)CSA Certificate:c/SA_254821cull Certificate:c/UR_25056Declaration of Conformity - CE:1 SND25042C1000EAC certificate:LRS_0620042UR Certificate:UR_E352056Declarations SColoudationsClassificationsColoudationsClassificationsColoudationsClassificationsColoudationsClassification SColoudation relayClassification Code:KETIM 4:EC001437 - Switching relayETIM 5:EC001437 - Switching relay	Package Level 1 Width:	73 mm
Package Level 1 Gross Weight: 0.23 kg Package Level 1 EAN: 3472596450052 Technical Function: Function: Boxed interface relay R600 Sub-Function: Relay with built in LED Output: 1 c/o (SPDT) contact Output Signal: 5 250 V AC / 1 mA 6 A Rated Control Supply Voltage (Us): 24 V AC/DC Terminal Type: Screw Terminals Certificates and Declarations (Document Number) CSA Certificate: CSA Certificate: CSA_254821 cUR Certificate: cUR_E352056 Declaration of Conformity - CE: 1 SND225042C1000 EAC certificate: LR S_0620042 UR Certificate: UR_E352056 Declaration of Conformity - CE: 1 SND225042C1000 EAC certificate: UR_E352056 Certificate: UR_E352056 Classification: UR_E352056 Certificate: UR_E352056 Classifications Coloutage Classifications Coloutage Diject Classification Code: K ETIM 4: EC001437 - Switching relay ETIM 5:	Package Level 1 Height:	71 mm
Package Level 1 EAN: 3472596450052 Technical Function: Boxed interface relay R600 Sub-Function: Relay with built in LED Output: 1 c/o (SPDT) contact Output Signal: 5 250 V AC / 1 mA 6 A Rated Control Supply Voltage (Us): 24 V AC/DC Terminal Type: Screw Terminals Certificates and Declarations (Document Number) CSA Certificate: CSA Certificate: CJR_254821 cUR Certificate: CJR_25042C1000 EAC Certificate: EAC_RU_C-FR.ME77.B.01634 LR Certificate: UR_E352056 Declarations UW_E352042C UR Certificate: UR_E352056 Certificate: UR_E352056 Classification: UW_E352056 Classifications UW_E352056 Classifications UW_E352056 Classifications UW_E352056 Classifications UW_E352056 Classifications UW_E352056 Diject Classification Code: K ETIM 4: EC001437 - Switching relay ETIM 5: EC001437 - Switching relay	Package Level 1 Length:	80 mm
Technical Function: Boxed interface relay R600 Sub-Function: Relay with built in LED Output: 1 c/o (SPDT) contact Output Signal: 5 250 V AC / 1 mA 6 A Rated Control Supply Voltage (Us): 24 V AC/DC Terminal Type: Screw Terminals Certificates and Declarations (Document Number) CSA Certificate: CSA Certificate: CSA_254821 cUR_E352056 Celaration of Conformity - CE: Declaration of Conformity - CE: 1SND225042C1000 EAC Certificate: EAC_RU_C-FR.ME77.B.01634 LR Certificate: UR_S_0620042 UR Certificate: UR_E352056 Classifications Object Classification Code: M K ETIM 4: EC001437 - Switching relay ETIM 5: EC001437 - Switching relay	Package Level 1 Gross Weight:	0.23 kg
Function: Boxed interface relay R600 Sub-Function: Relay with built in LED Output: 1 c/o (SPDT) contact Output Signal: 5 250 V AC / 1 mA 6 A Rated Control Supply Voltage (Us): 24 V AC/DC Terminal Type: Screw Terminals Certificates and Declarations (Document Number) CSA Certificate: CSA Certificate: CJR 254821 cUR Certificate: CUR E352056 Declaration of Conformity - CE: 1 SND225042C1000 EAC Certificate: EAC_RU_C-FR.ME77.B.01634 LR Certificate: UR Screw Terminals Classifications Output Certificate: Object Classification Code: K ETIM 4: EC001437 - Switching relay ETIM 5: EC001437 - Switching relay	Package Level 1 EAN:	3472596450052
Sub-Function:Relay with built in LEDOutput:1 c/o (SPDT) contactOutput Signal:5 250 V AC / 1 mA 6 ARated Control Supply Voltage (Us):24 V AC/DCTerminal Type:Screw TerminalsCertificates and Declarations (Document Number)CSA Certificate:CSA_254821cUR Certificate:cUR_E352056Declaration of Conformity - CE:1SND225042C1000EAC Certificate:EAC_RU_C-FR.ME77.B.01634LR Certificate:UR_E352056Object ClassificationsUR_E352056ClassificationsECO01437 - Switching relayETIM 4:EC001437 - Switching relayETIM 5:EC001437 - Switching relay	Technical	
Output:1 c/o (SPDT) contactOutput Signal:5 250 V AC / 1 mA 6 ARated Control Supply Voltage (Us):24 V AC/DCTerminal Type:Screw TerminalsCertificates and Declarations (Document Number)CSA Certificate:CSA_254821cUR Certificate:cUR_E352056Declaration of Conformity - CE:1 SIND225042C1000EAC Certificate:LR S_0620042UR Certificate:UR_E352056ClassificationsUR_E352056Object Classification Code:KETIM 4:EC001437 - Switching relayETIM 5:EC001437 - Switching relay	Function:	Boxed interface relay R600
Output Signal: 5 250 V AC / 1 mA 6 A Rated Control Supply Voltage (Us): 24 V AC/DC Terminal Type: Screw Terminals Certificates and Declarations (Document Number) CSA Certificate: CSA Certificate: CSA_254821 cUR Certificate: cUR_E352056 Declaration of Conformity - CE: 1SND225042C1000 EAC Certificate: EAC_RU_C-FR.ME77.B.01634 LR Certificate: UR_E352056 UR Certificate: UR_E352056 Classifications UR_E352056 Object Classification Code: K ETIM 4: EC001437 - Switching relay ETIM 5: EC001437 - Switching relay	Sub-Function:	Relay with built in LED
Rated Control Supply Voltage (Us): 24 V AC/DC Terminal Type: Screw Terminals Certificates and Declarations (Document Number) CSA Certificate: CSA_254821 cUR Certificate: cUR_E352056 Declaration of Conformity - CE: 1SND225042C1000 EAC Certificate: EAC_RU_C-FR.ME77.B.01634 LR Certificate: UR_E352056 Object Classifications UR_E352056 Classifications EC001437 - Switching relay ETIM 4: EC001437 - Switching relay	Output:	1 c/o (SPDT) contact
Terminal Type:Screw TerminalsCertificates and Declarations (Document Number)CSA Certificate:CSA_254821cUR Certificate:cUR_E352056Declaration of Conformity - CE:1SND225042C1000EAC Certificate:EAC_RU_C-FR.ME77.B.01634LR Certificate:LRS_0620042UR Certificate:UR_E352056ClassificationsObject Classification Code:KETIM 4:ETIM 4:EC001437 - Switching relayETIM 5:EC001437 - Switching relay	Output Signal:	5 250 V AC / 1 mA 6 A
Certificates and Declarations (Document Number)CSA Certificate:CSA_254821cUR Certificate:cUR_E352056Declaration of Conformity - CE:1SND225042C1000EAC Certificate:EAC_RU_C-FR.ME77.B.01634LR Certificate:LRS_0620042UR Certificate:UR_E352056ClassificationsObject Classification Code:KETIM 4:EC001437 - Switching relayETIM 5:EC001437 - Switching relay	Rated Control Supply Voltage (Us):	24 V AC/DC
CSA Certificate: CSA_254821 cUR Certificate: cUR_E352056 Declaration of Conformity - CE: 1SND225042C1000 EAC Certificate: EAC_RU_C-FR.ME77.B.01634 LR Certificate: LRS_0620042 UR Certificate: UR_E352056 Classifications Object Classification Code: K ETIM 4: EC001437 - Switching relay ETIM 5: EC001437 - Switching relay	Terminal Type:	Screw Terminals
CSA Certificate: CSA_254821 cUR Certificate: cUR_E352056 Declaration of Conformity - CE: 1SND225042C1000 EAC Certificate: EAC_RU_C-FR.ME77.B.01634 LR Certificate: LRS_0620042 UR Certificate: UR_E352056 Classifications Object Classification Code: K ETIM 4: EC001437 - Switching relay ETIM 5: EC001437 - Switching relay	Certificates and Declarations (Declarations)	ocument Number)
cUR Certificate: cUR_E352056 Declaration of Conformity - CE: 1SND225042C1000 EAC Certificate: EAC_RU_C-FR.ME77.B.01634 LR Certificate: LRS_0620042 UR Certificate: UR_E352056 Classifications Object Classification Code: K ETIM 4: EC001437 - Switching relay ETIM 5: EC001437 - Switching relay	· · · · · · · · · · · · · · · · · · ·	
Declaration of Conformity - CE: 1SND225042C1000 EAC Certificate: EAC_RU_C-FR.ME77.B.01634 LR Certificate: LRS_0620042 UR Certificate: UR_E352056 Classifications Object Classification Code: K ETIM 4: EC001437 - Switching relay ETIM 5: EC001437 - Switching relay		-
EAC Certificate: EAC_RU_C-FR.ME77.B.01634 LR Certificate: LRS_0620042 UR Certificate: UR_E352056 Classifications Object Classification Code: K ETIM 4: EC001437 - Switching relay ETIM 5: EC001437 - Switching relay	Declaration of Conformity - CE:	—
LR Certificate: LRS_0620042 UR Certificate: UR_E352056 Classifications Classification Code: Object Classification Code: K ETIM 4: EC001437 - Switching relay ETIM 5: EC001437 - Switching relay	-	EAC RU C-FR.ME77.B.01634
Classifications Object Classification Code: K ETIM 4: EC001437 - Switching relay ETIM 5: EC001437 - Switching relay	LR Certificate:	LRS 0620042
Object Classification Code: K ETIM 4: EC001437 - Switching relay ETIM 5: EC001437 - Switching relay	UR Certificate:	UR_E352056
ETIM 4:EC001437 - Switching relayETIM 5:EC001437 - Switching relay	Classifications	
ETIM 5: EC001437 - Switching relay	Object Classification Code:	К
ETIM 5: EC001437 - Switching relay	ETIM 4:	EC001437 - Switching relay
- · ·	ETIM 5:	EC001437 - Switching relay
	UNSPSC:	
eClass: 7.0 27371601	eClass:	7.0 27371601







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
RB121A-24VAC/DC Interface relay R600 1c/ o,A1-A2=24VAC/DC,250V/1mA-6A,LED	1SNA645005R0700	RB121A 24VAC/DC	Buy on EAN