



Automatización Eléctrica Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

DDA202 A-40/0,03 AP-R



Extended Product Type:	DDA202 A-40/0,03 AP-R		
Product ID:	2CSB202401R1400		
EAN:	8012542801207		
Catalog Description:	DDA202 A-40/0,03 AP-R - RCD Block		
Long Description:	The RCD block DDA200 series is suitable for assembly with MCBs S200 series. It assures protection against the effects of sinusoidal alternating and direct pulsating earth fault currents, providing the best compromise between safety and continuity in the service thank to the resistance to unwanted trippings. Protection against indirect contacts and additional protection against direct (with sensitivity = 30 mA) contacts. Applications: residential, commercial, industrial.		
Categories			
Products » Low Voltage Products a	and Systems » Modular DIN Rail Products » Residual Current Devices RCDs » Residua		
Current Devices RCD Blocks			
Ordering			
EAN:	8012542801207		
Minimum Order Quantity:	1 piece		
Customs Tariff Number:	85363030		
Dimensions			
Product Net Width:	0.070 m		
Product Net Height:	0.093 m		
Product Net Depth:	0.069 m		
Product Net Weight:	0.210 kg		
Container Information			
Package Level 1 Units:	1 piece		
Package Level 1 Width:	0.077 m		
Package Level 1 Height:	0.076 m		
Package Level 1 Length:	0.102 m		
Package Level 1 Gross Weight:	0.245 kg		
Package Level 1 EAN:	8012542801214		
Technical			
Standards:	EN 61009 Ann. G		
Operating Characteristic:	Instantaneous (APR High Immunity)		
Type of Residual Current:	A type		
Type er rædradar earrena			
Rated Residual Current:	30 mA		
	30 mA 40 A		
Rated Residual Current:			
Rated Residual Current: Rated Current (I _n):	40 A		
Rated Residual Current: Rated Current (I _n): Number of Poles:	40 A 2		
Rated Residual Current: Rated Current (I _n): Number of Poles: Power Loss:	40 A 2 3.2 W		
Rated Residual Current: Rated Current (I _n): Number of Poles: Power Loss: Rated Voltage (U _r):	40 A 2 3.2 W		
Rated Residual Current: Rated Current (I _n): Number of Poles: Power Loss: Rated Voltage (U _r): Environmental	40 A 2 3.2 W 230/400 V		
Rated Residual Current: Rated Current (I _n): Number of Poles: Power Loss: Rated Voltage (U _r): Environmental	40 A 2 3.2 W 230/400 V Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q3		
Rated Residual Current: Rated Current (I _n): Number of Poles: Power Loss: Rated Voltage (U _r): Environmental RoHS Status:	40 A 2 3.2 W 230/400 V Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q3		
Rated Residual Current: Rated Current (I _n): Number of Poles: Power Loss: Rated Voltage (U _r): Environmental RoHS Status: Certificates and Declarations (I	40 A 2 3.2 W 230/400 V Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q3 Document Number)		
Rated Residual Current: Rated Current (I _n): Number of Poles: Power Loss: Rated Voltage (U _r): Environmental RoHS Status: Certificates and Declarations (I Declaration of Conformity - CE:	40 A 2 3.2 W 230/400 V Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q3 Document Number) ITSCE127DDA200		
Rated Residual Current: Rated Current (I _n): Number of Poles: Power Loss: Rated Voltage (U _r): Environmental RoHS Status: Certificates and Declarations (I Declaration of Conformity - CE: RoHS Information:	40 A 2 3.2 W 230/400 V Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q3 Document Number) ITSCE127DDA200		







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
DDA202 A-40/0,03 AP-R - RCD Block	2CSB202401R1400	DDA202A40/0,03APR	Buy on EAN