



## Automatización Eléctrica Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

## F202 A-63/0,5



## **General Information**

| Extended Product Type: | F202 A-63/0,5  |
|------------------------|--|
| Product ID:            | 2CSF202101R4630  |
| EAN:                   | 8012542783305  |
| Catalog Description:   | F202 A-63/0,5 Residual Current Dev.  |
| Long Description:      | The RCCBs F200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. |

## Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » Residual Current Devices RCDs » Residual Current Devices RCDs

| Ordering                         | 0040540700005   |
|----------------------------------|---|
| EAN:                             | 8012542783305   |
| Minimum Order Quantity:          | 1 piece   |
| Customs Tariff Number:           | 85363030  |
| Dimensions                       |   |
| Product Net Width:               | 0.035 m   |
| Product Net Height:              | 0.085 m   |
| Product Net Depth:               | 0.069 m   |
| Product Net Weight:              | 0.200 kg  |
| Container Information            |   |
| Package Level 1 Units:           | 1 piece   |
| Package Level 1 Width:           | 0.041 m   |
| Package Level 1 Height:          | 0.078 m   |
| Package Level 1 Length:          | 0.096 m   |
| Package Level 1 Gross Weight:    | 0.225 kg  |
| Package Level 1 EAN:             | 8012542783305   |
| Technical                        |   |
| Standards:                       | EN 61008<br>UL 1053   |
| Operating Characteristic:        | Instantaneous   |
| Type of Residual Current:        | A type  |
| Rated Residual Current:          | 500 mA  |
| Rated Current (In):              | 63 A  |
| Number of Poles:                 | 2   |
| Power Loss:                      | at Rated Operating Conditions per Pole 3.2 W  |
| Rated Voltage (U <sub>r</sub> ): | 230/400 V   |
| Environmental                    |   |
| RoHS Status:                     | Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q3 |
| Certificates and Declarations (  | Document Number)  |
| Declaration of Conformity - CE:  | ITSCE116F200  |
| RoHS Information:                | 2CSC423001K0201   |
|                                  |   |
| Classifications                  |   |
| Object Classification Code:      | Q   |
| ETIM 4:                          | EC000003 - Residual current circuit breaker (RCCB)                                    |
| ETIM 5:                          | EC000003 - Residual current circuit breaker (RCCB)                                    |







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

| Product                             | Code            | Reference    | Product link |
|-------------------------------------|-----------------|--------------|--------------|
| F202 A-63/0,5 Residual Current Dev. | 2CSF202101R4630 | F202A-63/0,5 | Buy on EAN   |