



Automatización Eléctrica Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

E 91/32 PV



General Information

Extended Product Type:	E 91/32 PV
Product ID:	2CSM204713R1801
EAN:	8012542047131
Catalog Description:	E 91/32 PV Fuse holder
Long Description:	E 91/32 PV is a fuseholder for overcurrent and short circuit protection in PV applications. No blown fuse indicator.

Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » Modular DIN Rail Components MDRCs » Fuse Holders

Ordering	
EAN:	8012542047131
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85361010
Dimensions	
Product Net Width:	0.018 m
Product Net Height:	0.085 m
Product Net Depth:	0.064 m
Product Net Weight:	0.061 kg
Container Information	
Package Level 1 Units:	6 piece
Package Level 1 Width:	0.105 m
Package Level 1 Height:	0.085 m
Package Level 1 Length:	0.064 m
Package Level 1 Gross Weight:	0.369 kg
Package Level 1 EAN:	8012542047148
Technical	
Dimensions:	1 module
Rated Primary Current (Ipn):	32 A
reacear minary ourient (ipn).	02 / X
Number of Poles:	1
Number of Poles:	1
Number of Protected Poles:	1
Number of Protected Poles: Voltage Range:	1 1000 V DC
Number of Protected Poles:	1
Number of Protected Poles: Voltage Range:	1 1000 V DC
Number of Protected Poles: Voltage Range: Power Loss:	1 1000 V DC
Number of Protected Poles: Voltage Range: Power Loss: Environmental RoHS Status:	1 1000 V DC at Rated Operating Conditions per Pole 3 W Following EU Directive 2011/65/EC
Number of Protected Poles: Voltage Range: Power Loss: Environmental RoHS Status: Certificates and Declarations (1 1000 V DC at Rated Operating Conditions per Pole 3 W Following EU Directive 2011/65/EC Document Number)
Number of Protected Poles: Voltage Range: Power Loss: Environmental RoHS Status:	1 1000 V DC at Rated Operating Conditions per Pole 3 W Following EU Directive 2011/65/EC
Number of Protected Poles: Voltage Range: Power Loss: Environmental RoHS Status: Certificates and Declarations (Declaration of Conformity - CE:	1 1000 V DC at Rated Operating Conditions per Pole 3 W Following EU Directive 2011/65/EC Document Number) ITSCE174E90FD
Number of Protected Poles: Voltage Range: Power Loss: Environmental RoHS Status: Certificates and Declarations (Declaration of Conformity - CE:	1 1000 V DC at Rated Operating Conditions per Pole 3 W Following EU Directive 2011/65/EC Document Number) ITSCE174E90FD
Number of Protected Poles: Voltage Range: Power Loss: Environmental RoHS Status: Certificates and Declarations (Declaration of Conformity - CE: RoHS Information:	1 1000 V DC at Rated Operating Conditions per Pole 3 W Following EU Directive 2011/65/EC Document Number) ITSCE174E90FD
Number of Protected Poles: Voltage Range: Power Loss: Environmental RoHS Status: Certificates and Declarations (Declaration of Conformity - CE: RoHS Information: Classifications	1 1000 V DC at Rated Operating Conditions per Pole 3 W Following EU Directive 2011/65/EC Document Number) ITSCE174E90FD 2CSC444011K2701
Number of Protected Poles: Voltage Range: Power Loss: Environmental RoHS Status: Certificates and Declarations (Declaration of Conformity - CE: RoHS Information: Classifications Object Classification Code:	1 1000 V DC at Rated Operating Conditions per Pole 3 W Following EU Directive 2011/65/EC Document Number) ITSCE174E90FD 2CSC444011K2701 F







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
E 91/32 PV Fuse holder	2CSM204713R1801	E91/32PV	Buy on EAN