



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

| | |
|------------------------|---|
| Extended Product Type: | DS201 C40 APR30 |
| Product ID: | 2CSR255440R1404 |
| EAN: | 8012542998006 |
| Catalog Description: | DS201 C40 APR30 - RCBO |
| Long Description: | The DS201 series RCBO is a 1P+N in two-modules device for the protection of end user single-phase circuits against overload and short-circuit currents; provides an optimal trade-off between safety and continuity of service, thanks to the resistance to unwanted trippings; protection against indirect contacts and additional protection against direct contacts (with sensitivity = 30 mA); protection and isolation of resistive and inductive loads. |

Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » Residual Current Devices RCDs » Residual Current Circuit Breakers with Overcurrent Protection RCBO

Ordering

| | |
|-------------------------|---------------|
| EAN: | 8012542998006 |
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85363030 |

Dimensions

| | |
|---------------------|----------|
| Product Net Width: | 0.035 m |
| Product Net Height: | 0.085 m |
| Product Net Depth: | 0.069 m |
| Product Net Weight: | 0.239 kg |

Container Information

| | |
|-------------------------------|---------------|
| Package Level 1 Units: | 5 piece |
| Package Level 1 Width: | 0.253 m |
| Package Level 1 Height: | 0.088 m |
| Package Level 1 Length: | 0.108 m |
| Package Level 1 Gross Weight: | 1.446 kg |
| Package Level 1 EAN: | 8012542998013 |

Technical

| | |
|--|--|
| Standards: | IEC 61009-1 IEC 61009-2-1 EN 61009-1 EN 61009-2-1 |
| Type of Residual Current: | A type |
| Rated Residual Current: | 30 mA |
| Tripping Characteristic: | C |
| Rated Current (I _n): | 40 A |
| Number of Poles: | 2 |
| Number of Protected Poles: | 1 |
| Rated Short-Circuit Capacity (I _{cn}): | (230 / 400 V AC) 6 kA |
| Position of Neutral Terminals: | Right |
| Power Loss: | 8.6 W |

Environmental

| | |
|--------------|---|
| RoHS Status: | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
|--------------|---|

Certificates and Declarations (Document Number)

| | |
|---------------------------------|-----------------|
| Declaration of Conformity - CE: | 2CSC421001D2702 |
| RoHS Information: | 2CSC422002K0201 |

Classifications

| | |
|-----------------------------|--|
| Object Classification Code: | Q |
| ETIM 4: | EC000905 - Earth leakage circuit breaker |
| ETIM 5: | EC000905 - Earth leakage circuit breaker |





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| Product | Code | Reference | Product link |
|------------------------|-----------------|------------------|----------------------------|
| DS201 C40 APR30 - RCBO | 2CSR255440R1404 | DS201C40APR30 | Buy on EAN |