



Automatización Eléctrica Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

SN201 L-C40



General Information

Extended Product Type:	SN201 L-C40
Product ID:	2CSS245101R0404
EAN:	8012542089056
Catalog Description:	Miniature circuit breaker - SN201 - 2P - C - 40 A
Long Description:	The SN201 series miniature circuit breaker is a 1P+N single-module device for the protection of circuits against overload and short circuit. It is suitable for the application in final distribution and protection of long cable lenghts in TN and IT systems

Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » Miniature Circuit Breakers MCBs

EAN:	8012542089056				
Minimum Order Quantity:	1 piece				
Customs Tariff Number:	85362010				
Dimensions					
Product Net Width:	0.018 m				
Product Net Depth:	0.069 m				
Product Net Height:	0.085 m				
Product Net Weight:	0.110 kg				
Container Information					
Package Level 1 Units:	6 piece				
Package Level 1 Width:	0.11 m				
Package Level 1 Length:	0.092 m				
Package Level 1 Height:	0.075 m				
Package Level 1 Gross Weight:	0.684 kg				
Package Level 1 EAN:	8012542089063				
Environmental					
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment				
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment				
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment IEC/EN 60898-1				
RoHS Status: Technical					
RoHS Status: Technical Standards:	IEC/EN 60898-1				
RoHS Status: Technical Standards: Number of Poles:	IEC/EN 60898-1 2				
RoHS Status: Technical Standards: Number of Poles: Tripping Characteristic:	IEC/EN 60898-1 2 C				
RoHS Status: Technical Standards: Number of Poles: Tripping Characteristic: Rated Current (I _n):	IEC/EN 60898-1 2 C 40 A				
RoHS Status: Technical Standards: Number of Poles: Tripping Characteristic: Rated Current (I _n): Power Loss: Rated Short-Circuit Capacity (I _{cn}):	IEC/EN 60898-1 2 C 40 A at Rated Operating Conditions per Pole 7.5 W (230 / 400 V AC) 4.5 kA				
RoHS Status: Technical Standards: Number of Poles: Tripping Characteristic: Rated Current (I _n): Power Loss:	IEC/EN 60898-1 2 C 40 A at Rated Operating Conditions per Pole 7.5 W (230 / 400 V AC) 4.5 kA				

Classifications

erabolitioatierito	
ETIM 4:	EC000042 - Miniature circuit breaker (MCB)
ETIM 5:	EC000042 - Miniature circuit breaker (MCB)
Object Classification Code:	Q







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
Miniature circuit breaker - SN201 - 2P - C - 40 A	2CSS245101R0404	SN201L-C40	Buy on EAN