



**Electric Automation**  
Automation specialists

Reference: OTP125BA4U  
Code: 1SCA022459R7160

OTP125BA4U Enclosed switch

Buy it at Electric Automation Network



Enclosed switch 4-p.400V AC23A 50A AC22A 125A Plastic enclosure IP65 Yellow-red Selector handle

### Ordering

EAN:	6417019143248
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

### Dimensions

Product Net Width:	200 mm
Product Net Height:	400 mm
Product Net Depth:	140 mm
Product Net Weight:	2.5 kg

### Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	203 mm
Package Level 1 Height:	187 mm
Package Level 1 Length:	407 mm
Package Level 1 Gross Weight:	2.6 kg

Package Level 1 EAN:	6417019143248
----------------------	---------------

## Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q4
--------------	---

## Additional Information

Conventional Thermal Current ( $I_{the}$ ):	Fully Enclosed 100 A
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	4
Pollution Degree:	3
Product Main Type:	OT125
Product Name:	Enclosed switch
Rated Operational Current AC-22A ( $I_e$ ):	(500 V) 125 A (690 V) 125 A
Rated Operational Current AC-23A ( $I_e$ ):	(380 ... 415 V) 90 A (500 V) 70 A (690 V) 50 A
Rated Operational Voltage:	750 V

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SCC340009C0201
Declaration of Conformity - CE:	1SCC340003D0203

## Classifications

ETIM 5:	EC000249 - Protection switch disconnecter housing
Object Classification Code:	Q