



**Electric Automation**  
Automation specialists

Reference: OT200E12P  
Code: 1SCA022721R3990

OT200E12P switch-disconnector

Buy it at Electric Automation Network



Including a black ON-OFF plastic handle and shaft as standard. The handle is IP65 protected, padlockable in the OFF-position and with door interlock in the ON-position. The shaft is adjustable for a range of installation depths.

## Ordering

EAN:	6417019231761
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

## Dimensions

Product Net Width:	186 mm
Product Net Height:	150 mm
Product Net Depth:	83 mm
Product Net Weight:	1.6 kg

## Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	160 mm
Package Level 1 Height:	96 mm
Package Level 1 Length:	210 mm
Package Level 1 Gross Weight:	1.6 kg
Package Level 1 EAN:	6417019231761

## Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-06-01
--------------	--

## Additional Information

Conventional Free-air Thermal Current ( $I_{th}$ ):	$q = 40 \text{ }^\circ\text{C}$ 200 A
Conventional Thermal Current ( $I_{the}$ ):	Fully Enclosed 200 A
Dielectric Test Voltage:	10000 V
Earthing Switch Type:	No Additional Type
Handle Type:	Pistol
IIT Publishing Status:	Level 0 - Information enabled
Includes:	Handle and Shaft
Mounting Type:	Normal
Number of Poles:	3
Operating Mechanism:	Mechanism between the poles
Operating Mode:	Front Operated
Pollution Degree:	3
Position of Line Terminals:	Top In - Bottom Out
Power Loss:	at Rated Operating Conditions per Pole 4 W
Product Main Type:	OT200
Product Name:	Switch-disconnector
Rated Impulse Withstand Voltage ( $U_{imp}$ ):	12 kV
Rated Insulation Voltage ( $U_i$ ):	1000 V
Rated Operational Current AC-21A ( $I_e$ ):	(380 ... 415 V) 200 A (690 V) 200 A (500 V) 200 A
Rated Operational Current AC-21B ( $I_e$ ):	(690 V) 200 A (500 V) 200 A (380 ... 415 V) 200 A
Rated Operational Current AC-22A ( $I_e$ ):	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A
Rated Operational Current AC-22B ( $I_e$ ):	(690 V) 200 A (500 V) 200 A (415 V) 200 A
Rated Operational Current AC-23A ( $I_e$ ):	(500 V) 200 A (690 V) 200 A (380 ... 415 V) 200 A
Rated Operational Current AC-23B ( $I_e$ ):	(690 V) 200 A (500 V) 200 A (380 ... 415 V) 200 A

Rated Operational Power AC-23A ( $P_e$ ):	(690 V) 200 kW (500 V) 132 kW (400 ... 415 V) 110 kW (400 V) 110 kW (220 ... 240 V) 60 kW
Rated Short-time Withstand Current ( $I_{cw}$ ):	for 1 s 8000 A
Special Functions:	No
Standards:	IEC
Terminal Type:	Lug terminals
Terminal Width:	20 mm
Tightening Torque:	Wire-Clamp 15 ... 22 N·m

### Certificates and Declarations (Document Number)

BV Certificate:	1SCC301103D0201
Data Sheet, Technical Information:	1SCC301020C0201
Declaration of Conformity - CE:	1SCC301131D0202
GL Certificate:	1SCC301139D0201
LR Certificate:	1SCC301144D0201
RoHS Information:	1SCC301149D0202

### Classifications

E-nummer:	3171158
ETIM 5:	EC000216 - Switch disconnecter
Object Classification Code:	Q