



Electric Automation
Automation specialists

Reference: OT315E04CP
Code: 1SCA022775R7150

OT315E04CP CHANGE-OVER SWITCH

Buy it at Electric Automation Network



Including a black plastic IP65 I-0-II pistol type handle (see the table below), shaft and bolt set for the cable connection. Handle padlockable in the 0-position, door interlock in the I- and lipositions and when padlocked.

Ordering

EAN:	6417019252469
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Dimensions

Product Net Width:	265 mm
Product Net Height:	185 mm
Product Net Depth:	203 mm
Product Net Weight:	4.1 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	240 mm
Package Level 1 Height:	218 mm
Package Level 1 Length:	326 mm
Package Level 1 Gross Weight:	7.57 kg
Package Level 1 EAN:	6417019252469

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q4
--------------	---

Additional Information

Conventional Free-air Thermal Current (I_{th}):	q = 40 °C 315 A
Conventional Thermal Current (I_{the}):	Fully Enclosed 315 A
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	4
Operating Mechanism:	Mechanism at the end of the switch
Pollution Degree:	3
Power Loss:	6.5 W
Product Main Type:	OT315_C
Product Name:	CHANGE-OVER SWITCH
Rated Impulse Withstand Voltage (U_{imp}):	12 kV
Rated Insulation Voltage (U_i):	1000 V
Rated Operational Current AC-21A (I_e):	(500 V) 315 A (690 V) 315 A
Rated Operational Current AC-22A (I_e):	(500 V) 315 A (690 V) 315 A
Rated Operational Current AC-23A (I_e):	(380 ... 415 V) 315 A (500 V) 315 A (690 V) 315 A
Rated Operational Power AC-23A (P_e):	(220 ... 240 V) 100 kW (400 V) 160 kW (500 V) 220 kW (690 V) 315 kW
Rated Operational Voltage:	1000 V
Rated Short-time Withstand Current (I_{cw}):	for 1 s 15 kiloampere rms
Terminal Width:	25 mm
Tightening Torque:	acc. IEC 60947-1 30 ... 44 N·m

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SCC303003C0201
Declaration of Conformity - CE:	1SCC303004D0202
RoHS Information:	1SCC301149D0202

Classifications

ETIM 5:	EC000216 - Switch disconnecter
Object Classification Code:	Q