



Electric Automation
Automation specialists

Reference: OT1200U
Code: 1SCA022860R6910

OT1200U03P Non-fusible disconnect switch

Buy it at Electric Automation Network



Including handle: NEMA 1, 3R, 12, IP65 and shaft

Ordering

EAN:	6417019309408
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Dimensions

Product Net Width:	335 mm
Product Net Height:	372 mm
Product Net Depth:	127 mm
Product Net Weight:	17 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	400 mm
Package Level 1 Height:	170 mm
Package Level 1 Length:	435 mm
Package Level 1 Gross Weight:	18.5 kg
Package Level 1 EAN:	6417019309408

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q4
--------------	---

Technical UL/CSA

Ampere Rating UL/CSA:	1200 A
-----------------------	--------

Additional Information

Earthing Switch Type:	No Additional Type
Handle Type:	Pistol
IIT Publishing Status:	Level 0 - Information enabled
Includes:	Handle and Shaft
Mounting Type:	Normal
Number of Poles:	3
Operating Mechanism:	Mechanism at the end of the switch
Operating Mode:	Front Operated
Pollution Degree:	3
Power Loss:	29 W
Product Main Type:	OT1200U
Product Name:	Switch-disconnector
Rated Impulse Withstand Voltage (U_{imp}):	12 kV
Rated Insulation Voltage (U_i):	1000 V
Rated Operational Current AC-22A (I_e):	(380 ... 415 V) 1600 A (500 V) 1600 A (690 V) 1600 A
Rated Operational Current AC-23A (I_e):	(380 ... 415 V) 1250 A (500 V) 1250 A (690 V) 1250 A
Rated Operational Voltage:	1000 V
Rated Short-time Withstand Current (I_{cw}):	for 1 s 50 kiloampere rms
Special Functions:	No
Standards:	IEC&UL
Terminal Type:	Lug terminals

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SCC301020C0201
Declaration of Conformity - CE:	1SCC301161D0202

Classifications

ETIM 5:	EC000216 - Switch disconnecter
Object Classification Code:	Q