



**Electric Automation**  
Automation specialists

Reference: OSM250D3M230C  
Code: 1SCA104295R1001

OSM250D3M230C Motorized switch fuse

Buy it at Electric Automation Network



Including a handle for manual operation, bolt kit with nut and washers for all terminals (100A...1250A), male connectors for control circuit and a handle and spare fuse storage clip.

## Ordering

EAN:	6417019384955
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85389099

## Dimensions

Product Net Width:	354 mm
Product Net Height:	206 mm
Product Net Depth:	193 mm
Product Net Weight:	6.7 kg

## Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	215 mm
Package Level 1 Height:	215 mm
Package Level 1 Length:	395 mm
Package Level 1 Gross Weight:	6.7 kg
Package Level 1 EAN:	6417019384955

## Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-07-01
--------------	--

## Additional Information

Conventional Free-air Thermal Current ( $I_{th}$ ):	q = 40 °C 250 A
Fuse Size:	0, 1
Fuse System:	DIN
Fuse Type:	DIN
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	3
Operating Mechanism:	Mechanism at the end of the switch
Pollution Degree:	3
Position of Line Terminals:	Top In - Bottom Out
Power Loss:	at Rated Operating Conditions per Pole 13 W
Product Main Type:	OSM250
Product Name:	Motorized switch fuse
Rated Impulse Withstand Voltage ( $U_{imp}$ ):	12 kV
Rated Insulation Voltage ( $U_i$ ):	1000 V
Rated Operational Current AC-21A ( $I_e$ ):	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-22A ( $I_e$ ):	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-23A ( $I_e$ ):	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Power AC-23A ( $P_e$ ):	(220 ... 240 V) 70 kW (400 V) 140 kW (415 V) 145 kW (500 V) 170 kW (690 V) 250 kW
Rated Operational Voltage:	1000 V
Rated Short-time Withstand Current ( $I_{cw}$ ):	for 1 s 8 kiloampere rms

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SCC311013C0201
------------------------------------	-----------------

## Classifications

ETIM 5:	EC001040 - Fuse switch disconnecter
Object Classification Code:	Q