



Electric Automation
Automation specialists

Reference: OT40F4C
Code: 1SCA104934R1001

OT40F4C CHANGE-OVER SWITCH

[Buy it at Electric Automation Network](#)



Handle and shaft has to be ordered separately

Ordering

EAN:	6417019390741
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Dimensions

Product Net Width:	96 mm
Product Net Height:	68 mm
Product Net Depth:	68 mm
Product Net Weight:	0.31 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	80 mm
Package Level 1 Height:	79 mm
Package Level 1 Length:	108 mm
Package Level 1 Gross Weight:	0.76 kg
Package Level 1 EAN:	6417019390741

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q4
--------------	---

Technical UL/CSA

Ampere Rating UL/CSA:	40 A
Horsepower Rating UL/CSA:	(acc. to UL 200 V) 10 Hp (acc. to UL 208 V) 10 Hp (acc. to UL 240 V) 10 Hp (acc. to UL 480 V) 20 Hp (acc. to UL 600 V) 25 Hp

Additional Information

Cable Cross-Section:	0.75...10 mm ²
Conventional Free-air Thermal Current (I_{th}):	q = 40 °C 40 A
Conventional Thermal Current (I_{the}):	Fully Enclosed 40 A
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	4
Operating Mechanism:	Mechanism between the poles
Pollution Degree:	3
Position of Line Terminals:	Top In - Bottom Out
Power Loss:	1.6 W
Product Main Type:	OT40_C
Product Name:	CHANGE-OVER SWITCH
Rated Impulse Withstand Voltage (U_{imp}):	8 kV
Rated Insulation Voltage (U_i):	750 V
Rated Operational Current AC-21A (I_e):	(500 V) 40 A (690 V) 40 A
Rated Operational Current AC-22A (I_e):	(500 V) 40 A (690 V) 40 A
Rated Operational Current AC-23A (I_e):	(380 ... 415 V) 23 A (500 V) 23 A (690 V) 12 A
Rated Operational Power AC-23A (P_e):	(220 ... 240 V) 5.5 kW (400 V) 11 kW (500 V) 11 kW (690 V) 11 kW
Rated Operational Voltage:	750 V
Rated Short-time Withstand Current (I_{cw}):	for 1 s 0.5 kiloampere rms

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SCC303003C0201
Declaration of Conformity - CE:	1SCC303019D0201

RoHS Information:	1SCC301183D0201
-------------------	-----------------

Classifications

ETIM 5:	EC000216 - Switch disconnecter
Object Classification Code:	Q