



**Electric Automation**  
Automation specialists

Reference: E4H/MS  
Code: 1SDA037548R1

E4H/MS 4000 3p F HR

Buy it at Electric Automation Network



C.BREAKER SWITCH-DISCONNECTOR E4H/MS 4000A THREE-POLE FIXED WITH TERMINALES REAR HORIZONTAL

### Ordering

|                         |               |
|-------------------------|---------------|
| EAN:                    | 8015644375485 |
| Minimum Order Quantity: | 1 piece       |
| Customs Tariff Number:  | 85362090      |

### Dimensions

|                     |         |
|---------------------|---------|
| Product Net Width:  | 515 mm  |
| Product Net Height: | 600 mm  |
| Product Net Length: | 785 mm  |
| Product Net Depth:  | 0.302 m |
| Product Net Weight: | 106 kg  |

### Container Information

|                               |               |
|-------------------------------|---------------|
| Package Level 1 Units:        | 1 piece       |
| Package Level 1 Height:       | 600 mm        |
| Package Level 1 Length:       | 515 mm        |
| Package Level 1 Gross Weight: | 124 kg        |
| Package Level 1 EAN:          | 8015644375485 |

## Environmental

|              |                       |
|--------------|-----------------------|
| RoHS Status: | No declaration needed |
|--------------|-----------------------|

## Additional Information

|  |                               |
|--|-------------------------------|
| Electrical Durability:                             | 5000                          |
| IIT Publishing Status:                             | Level 0 - Information enabled |
| Number of Poles:                                   | 3                             |
| Power Loss:  | 360 W                         |
| Product Main Type:                                 | SACE Emax Old                 |
| Product Name:                                      | Switch-disconnector           |
| Product Type:                                      | SD                            |
| Rated Current ( $I_n$ ):                           | 4000 A                        |
| Rated Operational Voltage:                         | 690 V AC                      |
| Standards:   | IEC-947-3                     |
| Sub-type:  | E4                            |
| Suitable For:                                      | Emax E4                       |
| Suitable for Product Class:                        | Emax                          |
| Terminal Connection Type:                          | Rear flat Horizontal          |
| Test Voltage at Industrial Frequency for 1 Minute: | 3500 V                        |
| Version:   | Fixed                         |

## Certificates and Declarations (Document Number)

|                                    |                 |
|------------------------------------|-----------------|
| Data Sheet, Technical Information: | 1SDC200001D0201 |
| Declaration of Conformity - CE:    | 1SDL000162R0045 |
| RoHS Information:                  | 1SDL000197R0001 |

## Classifications

|                             |   |
|-----------------------------|---|
| ETIM 4:                     | EC000228 - Power circuit-breaker for trafo/generator/<br>installation prot. |
| ETIM 5:                     | EC000228 - Power circuit-breaker for trafo/generator/<br>installation prot. |
| Object Classification Code: | Q   |