



**Electric Automation**  
Automation specialists

Reference: T3D250  
Code: 1SDA051327R1

T3D 250 3p F F

Buy it at Electric Automation Network



SWITCH-DISCONNECTOR TMAX T3D 250 FIXED THREE-POLE WITH FRONT TERMINALS

### Ordering

EAN:	8015644517489
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

### Dimensions

Product Net Width:	105 mm
Product Net Height:	150 mm
Product Net Depth:	70 mm
Product Net Weight:	1.6 kg

### Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	155 mm
Package Level 1 Height:	190 mm
Package Level 1 Length:	155 mm
Package Level 1 Gross Weight:	1.7 kg

Package Level 1 EAN:	8015644517489
----------------------	---------------

## Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-07-01
--------------	--

## Additional Information

IIT Publishing Status:	Level 0 - Information enabled
Mechanical Durability:	25000 cycle 120 cycles per hour
Number of Poles:	3
Power Loss:	at Rated Operating Conditions per Pole 17,8 W
Product Main Type:	SACE Tmax T
Product Name:	Switch-disconnector
Product Type:	SD
Rated Impulse Withstand Voltage ( $U_{imp}$ ):	8 kV
Rated Insulation Voltage ( $U_i$ ):	800 V
Rated Operational Voltage:	690 V AC 500 V DC
Rated Short-time Withstand Current ( $I_{cw}$ ):	for 1 s 3,6 A
Rated Uninterrupted Current ( $I_u$ ):	250 A
Standards:	IEC 60947
Sub-type:	T3
Suitable For:	T3
Suitable for Product Class:	Moulded Case Circuit Breakers
Terminal Connection Type:	Fixed Circuit-Breakers Front
Test Voltage at Industrial Frequency for 1 Minute:	3000 V
Test Voltage Max ( $U_{test}$ ):	3000 V
Version:	F

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SDC210004D0203
Data Sheet, Technical Information (Part 2):	1SDM000030R0001
Declaration of Conformity - CE:	1SDL000165R0003
RoHS Information:	1SDL000200R0001

## Classifications

Object Classification Code:	Q
UNSPSC:	39121100