



Electric Automation
Automation specialists

Reference: T2S160
Code: 1SDA053121R1

T2S 160 MF1 Im=13A 3p F F

Buy it at Electric Automation Network



C.BREAKER TMAX T2S 160 FIXED THREE-POLE WITH FRONT TERMINALS AND MAGNETIC RELEASE MF lu 1 A Im13 A

Ordering

| | |
|-------------------------|---------------|
| EAN: | 8015644539719 |
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85362090 |

Dimensions

| | |
|---------------------|--------|
| Product Net Width: | 90 mm |
| Product Net Height: | 130 mm |
| Product Net Depth: | 70 mm |
| Product Net Weight: | 1.1 kg |

Container Information

| | |
|-------------------------------|---------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 128 mm |
| Package Level 1 Height: | 135 mm |
| Package Level 1 Length: | 143 mm |
| Package Level 1 Gross Weight: | 1.2 kg |

| | |
|----------------------|---------------|
| Package Level 1 EAN: | 8015644539719 |
|----------------------|---------------|

Environmental

| | |
|--------------|------------------------------------------------------------------------------------------|
| RoHS Status: | Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-07-01 |
|--------------|------------------------------------------------------------------------------------------|

Additional Information

| | |
|--------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electrical Durability: | 8000 cycle 120 cycles per hour |
| IIT Publishing Status: | Level 0 - Information enabled |
| Mechanical Durability: | 25000 cycle 240 cycles per hour |
| Number of Poles: | 3 |
| Power Loss: | at Rated Operating Conditions per Pole 1,5 W |
| Product Main Type: | SACE Tmax T |
| Product Name: | Automatic Circuit Breaker |
| Product Type: | CB |
| Rated Current (I_n): | 1 A |
| Rated Impulse Withstand Voltage (U_{imp}): | 8 kV |
| Rated Insulation Voltage (U_i): | 800 V |
| Rated Operational Voltage: | 690 V AC 500 V DC |
| Rated Service Short-Circuit Breaking Capacity (I_{cs}): | (220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 45 kA (500 V AC) 30 kA (690 V AC) 7 kA |
| Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}): | (220 V AC) 8.5 kA (230 V AC) 8.5 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 45 kA (500 V AC) 30 kA (690 V AC) 7 kA (250 V DC) 2 Poles in Series 50 kA (250 V DC) 3 Poles in Series 55 kA (500 V DC) 3 Poles in Series 50 kA |
| Rated Uninterrupted Current (I_u): | 160 A |
| Release Type: | M |
| Standards: | IEC 60947 |
| Sub-type: | T2 |
| Suitable For: | T2 |

| | |
|----------------------------------------------------|---------------------------------|
| Suitable for Product Class: | Moulded Case Circuit Breakers |
| Terminal Connection Type: | Fixed Circuit-Breakers Front |
| Test Voltage at Industrial Frequency for 1 Minute: | 3000 V |
| Test Voltage Max (U_{test}): | 3000 V |
| Version: | F |

Certificates and Declarations (Document Number)

| | |
|------------------------------------|-----------------|
| Data Sheet, Technical Information: | 1SDC210004D0203 |
| Declaration of Conformity - CE: | 1SDL000165R0002 |
| GL Certificate: | 1SDL000163R0059 |
| RoHS Information: | 1SDL000200R0001 |

Classifications

| | |
|-----------------------------|----------|
| Object Classification Code: | Q |
| UNSPSC: | 39121100 |