



Electric Automation
Automation specialists

Reference: E2S2000
Code: 1SDA056024R1

E2S 2000 PR121/P-LI In=2000A 4p F HR

Buy it at Electric Automation Network



SACE EMAX CIRCUIT-BREAKER E2S 2000A FOUR-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LI R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Ordering

EAN:	8015644573645
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

Dimensions

Product Net Width:	386 mm
Product Net Height:	418 mm
Product Net Depth:	302 mm
Product Net Weight:	56 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	515 mm
Package Level 1 Height:	600 mm
Package Level 1 Length:	615 mm

Package Level 1 Gross Weight:	68 kg
Package Level 1 EAN:	8015644573645

Additional Information

Electrical Durability:	10000 cycle 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour
Number of Poles:	4
Power Loss:	at Rated Operating Conditions per Pole 180 W
Product Main Type:	SACE Emax
Product Name:	Automatic Circuit Breaker
Product Type:	CB
Rated Current (I_n):	2000 A
Rated Impulse Withstand Voltage (U_{imp}):	12 kV
Rated Insulation Voltage (U_i):	1000 V
Rated Operational Current (I_e):	2000 A
Rated Operational Voltage:	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 85 kA (400 V AC) 85 kA (415 V AC) 85 kA (440 V AC) 85 kA (500 V AC) 65 kA (660 V AC) 65 kA (690 V AC) 65 kA
Rated Short-time Withstand Current (I_{cw}):	for 1 s 85 kA for 3 s 85 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 85 kA (400 V AC) 85 kA (415 V AC) 85 kA (440 V AC) 85 kA (500 V AC) 65 kA (525 V AC) 65 kA (660 V AC) 65 kA (690 V AC) 65 kA
Rated Uninterrupted Current (I_u):	2000 A
Rated Voltage (U_r):	690 V
Release Type:	EL
Standards:	IEC 60947
Sub-type:	E2
Terminal Connection Type:	Fixed Circuit-Breakers Rear flat Horizontal
Version:	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SDC200006D0209
Declaration of Conformity - CE:	1SDL000165R0014

Classifications

ETIM 4:	EC000228 - Power circuit-breaker for trafo/generator/ installation prot.
ETIM 5:	EC000228 - Power circuit-breaker for trafo/generator/ installation prot.
Object Classification Code:	Q
UNSPSC:	39120000