



Electric Automation
Automation specialists

Reference: E3H1250
Code: 1SDA056378R1

E3H 1250 PR121/P-LSIG In=1250A 4p F
HR

Buy it at [Electric Automation Network](#)



SACE EMAX CIRCUIT-BREAKER E3H 1250A FOUR-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LSIG R1250 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Ordering

| | |
|-------------------------|---------------|
| EAN: | 8015644577186 |
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85362090 |

Dimensions

| | |
|---------------------|--------|
| Product Net Width: | 530 mm |
| Product Net Height: | 418 mm |
| Product Net Depth: | 302 mm |
| Product Net Weight: | 76 kg |

Container Information

| | |
|-------------------------|---------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 515 mm |
| Package Level 1 Height: | 600 mm |
| Package Level 1 Length: | 785 mm |

| | |
|-------------------------------|---------------|
| Package Level 1 Gross Weight: | 90 kg |
| Package Level 1 EAN: | 8015644577186 |

Additional Information

| | |
|--|--|
| Electrical Durability: | 12000 cycle 20 cycles per hour |
| Mechanical Durability: | 20000 cycle 60 cycles per hour |
| Number of Poles: | 4 |
| Power Loss: | at Rated Operating Conditions per Pole 60 W |
| Product Main Type: | SACE Emax |
| Product Name: | Automatic Circuit Breaker |
| Product Type: | CB |
| Rated Current (I_n): | 1250 A |
| Rated Impulse Withstand Voltage (U_{imp}): | 12 kV |
| Rated Insulation Voltage (U_i): | 1000 V |
| Rated Operational Current (I_e): | 1250 A |
| Rated Operational Voltage: | 690 V AC |
| Rated Service Short-Circuit Breaking Capacity (I_{cs}): | (220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 85 kA (400 V AC) 85 kA (415 V AC) 85 kA (440 V AC) 85 kA (500 V AC) 85 kA (660 V AC) 85 kA (690 V AC) 85 kA |
| Rated Short-time Withstand Current (I_{cw}): | for 1 s 100 kA for 3 s 100 kA |
| Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}): | (220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 100 kA (500 V AC) 100 kA (525 V AC) 100 kA (660 V AC) 85 kA (690 V AC) 85 kA |
| Rated Uninterrupted Current (I_u): | 1250 A |
| Rated Voltage (U_r): | 690 V |
| Release Type: | EL |
| Standards: | IEC 60947 |
| Sub-type: | E3 |
| Terminal Connection Type: | Fixed Circuit-Breakers Rear flat Horizontal |
| Version: | F |

Certificates and Declarations (Document Number)

| | |
|------------------------------------|-----------------|
| Data Sheet, Technical Information: | 1SDC200006D0209 |
| Declaration of Conformity - CE: | 1SDL000165R0015 |

Classifications

| | |
|-----------------------------|---|
| ETIM 4: | EC000228 - Power circuit-breaker for trafo/generator/ installation prot. |
| ETIM 5: | EC000228 - Power circuit-breaker for trafo/generator/ installation prot. |
| Object Classification Code: | Q |
| UNSPSC: | 39120000 |