



Electric Automation
Automation specialists

Reference: T7H1250
Code: 1SDA062901R1

T7H 1250 PR332/P LI In=1250A 3p F F

Buy it at Electric Automation Network



C.BREAKER TMAX T7H 1250 FIXED THREE-POLE WITH FRONT TERMINALS AND LEVER OPERATING MECHANISM AND SOLID-STATE RELEASE IN AC PR332/P-LI R 1250

Ordering

| | |
|-------------------------|---------------|
| EAN: | 8015644654504 |
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85362090 |

Dimensions

| | |
|---------------------|--------|
| Product Net Width: | 210 mm |
| Product Net Height: | 268 mm |
| Product Net Depth: | 154 mm |
| Product Net Weight: | 9.7 kg |

Container Information

| | |
|-------------------------------|---------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 280 mm |
| Package Level 1 Height: | 350 mm |
| Package Level 1 Length: | 360 mm |
| Package Level 1 Gross Weight: | 11.2 kg |

| | |
|----------------------|---------------|
| Package Level 1 EAN: | 8015644654504 |
|----------------------|---------------|

Environmental

| | |
|--------------|---------------------------------------------------------------------------------------|
| RoHS Status: | Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q2 |
|--------------|---------------------------------------------------------------------------------------|

Additional Information

| | |
|--------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of Poles: | 3 |
| Power Loss: | at Rated Operating Conditions per Pole 47 W |
| Product Main Type: | SACE Tmax T |
| Product Name: | Automatic Circuit Breaker |
| Product Type: | CB |
| Rated Current (I_n): | 1250 A |
| Rated Operational Voltage: | 690 V AC |
| Rated Service Short-Circuit Breaking Capacity (I_{cs}): | (220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 65 kA (500 V AC) 50 kA (690 V AC) 31 kA |
| Rated Short-time Withstand Current (I_{cw}): | for 1 s 20 A |
| Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}): | (220 V AC) 10 kA (230 V AC) 10 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 65 kA (500 V AC) 50 kA (690 V AC) 42 kA |
| Rated Uninterrupted Current (I_u): | 1250 A |
| Release Type: | EL |
| Standards: | IEC 60947 |
| Sub-type: | T7 |
| Suitable For: | T7 |
| Suitable for Product Class: | Moulded Case Circuit Breakers |
| Terminal Connection Type: | Fixed Circuit-Breakers Front |
| Version: | F |

Certificates and Declarations (Document Number)

| | |
|------------------------------------|-----------------|
| Data Sheet, Technical Information: | 1SDC210015D0201 |
| Declaration of Conformity - CE: | 1SDL000165R0007 |

| | |
|-------------------|-----------------|
| GL Certificate: | 1SDL000163R0053 |
| RoHS Information: | 1SDL000201R0001 |

Classifications

| | |
|-----------------------------|-----------------------------------------------------------------------------|
| ETIM 4: | EC000228 - Power circuit-breaker for trafo/generator/ installation prot. |
| ETIM 5: | EC000228 - Power circuit-breaker for trafo/generator/ installation prot. |
| Object Classification Code: | Q |
| UNSPSC: | 39121100 |