



Electric Automation
Automation specialists

Reference: T4L250 1000V
Code: 1SDA063420R1

T4L250 PR222DS/P-LSI In100 4p
FFC1000VAC

Buy it at Electric Automation Network



C.BREAKER TMAX T4L 250 1000V AC FIXED FOUR-POLE WITH FRONT TERMINALS FOR CABLE Cu AND SOLID-STATE RELEASE IN AC PR222DS/P-LSI R 100

Ordering

EAN:	8015644660390
Minimum Order Quantity:	1 piece

Container Information

Package Level 1 Units:	1 piece
------------------------	---------

Additional Information

Number of Poles:	4
Power Loss:	at Rated Operating Conditions per Pole 1.7 W
Product Main Type:	SACE Tmax T
Product Name:	Automatic Circuit Breaker
Product Type:	CB
Rated Current (I_n):	100 A
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(1000 V AC) 12 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(415 V AC) 120 kA (1000 V AC) 12 kA

Rated Uninterrupted Current (I _u):	250 A
Release Type:	EL
Standards:	IEC 60947
Sub-type:	T4
Terminal Connection Type:	Fixed Circuit-Breakers Front for Copper Cables
Version:	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SDC210023D0201
Declaration of Conformity - CE:	1SDL000165R0004
GL Certificate:	1SDL000163R0061

Classifications

ETIM 4:	EC000228 - Power circuit-breaker for trafo/generator/ installation prot.
ETIM 5:	EC000228 - Power circuit-breaker for trafo/generator/ installation prot.
Object Classification Code:	Q