



Electric Automation
Automation specialists

Reference: T5V630 1000V
Code: 1SDA063439R1

T5V 630 TMA 500-5000 3p F FC 1150V
AC

[Buy it at Electric Automation Network](#)



C.BREAKER TMAX T5V 630 1150V AC FIXED THREE-POLE WITH FRONT TERMINALS FOR CABLE Cu AND THERMOMAGNETIC RELEASE TMA R 500 I₃=2500...5000 A

Ordering

EAN:	8015644660635
Minimum Order Quantity:	1 piece

Container Information

Package Level 1 Units:	1 piece
------------------------	---------

Additional Information

Number of Poles:	3
Power Loss:	at Rated Operating Conditions per Pole 28.8 W
Product Main Type:	SACE Tmax T
Product Name:	Automatic Circuit Breaker
Product Type:	CB
Rated Current (I _n):	500 A
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(1000 V AC) 10 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(415 V AC) 200 kA (1000 V AC) 20 kA

Rated Uninterrupted Current (I _u):	630 A
Release Type:	TM
Standards:	IEC 60947
Sub-type:	T5
Terminal Connection Type:	Fixed Circuit-Breakers Front for Copper Cables
Version:	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SDC210023D0201
Declaration of Conformity - CE:	1SDL000165R0005

Classifications

ETIM 4:	EC000228 - Power circuit-breaker for trafo/generator/ installation prot.
ETIM 5:	EC000228 - Power circuit-breaker for trafo/generator/ installation prot.
Object Classification Code:	Q