



Electric Automation
Automation specialists

Reference: T8D2000
Code: 1SDA065753R1

T8D 2000 4p F F

Buy it at Electric Automation Network



SWITCH-DISCONNECTOR TMAX T8D 2000 FIXED FOUR-POLE WITH FRONT TERMINALS

Ordering

EAN:	8015644686642
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

Dimensions

Product Net Width:	553 mm
Product Net Height:	382 mm
Product Net Depth:	282 mm
Product Net Weight:	12.5 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	650 mm
Package Level 1 Height:	475 mm
Package Level 1 Length:	695 mm
Package Level 1 Gross Weight:	14 kg

Package Level 1 EAN:	8015644686642
----------------------	---------------

Additional Information

Electrical Durability:	4500 cycle 20 cycles per hour
Mechanical Durability:	15000 cycle 60 cycles per hour
Number of Poles:	4
Power Loss:	at Rated Operating Conditions per Pole 46 W
Product Main Type:	SACE Tmax T
Product Name:	Switch-disconnector
Product Type:	SD
Rated Impulse Withstand Voltage (U_{imp}):	8 kV
Rated Insulation Voltage (U_i):	1000 V
Rated Operational Voltage:	690 V AC
Rated Short-time Withstand Current (I_{cw}):	for 1 s 40 A
Rated Uninterrupted Current (I_u):	2000 A
Standards:	IEC 60947
Sub-type:	T8
Terminal Connection Type:	Fixed Circuit-Breakers Front
Version:	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SDC210023D0201
Declaration of Conformity - CE:	1SDL000165R0008

Classifications

ETIM 4:	EC000228 - Power circuit-breaker for trafo/generator/ installation prot.
ETIM 5:	EC000228 - Power circuit-breaker for trafo/generator/ installation prot.
Object Classification Code:	Q