



Electric Automation
Automation specialists

Reference: CP3-12G-10
Code: 1SFA619102R1212

PUSHBUTTON#CP3-12G-10#110-130V
AC/DC

[Buy it at Electric Automation Network](#)



Compact Pushbutton - Momentary - Extended - Green - Illuminated - Black plastic - 1NO

Ordering

EAN:	7320500381601
Minimum Order Quantity:	10 piece
Customs Tariff Number:	85369001

Dimensions

Product Net Width:	0.030 m
Product Net Height:	0.030 m
Product Net Depth:	0.055 m
Product Net Weight:	0.018 kg

Environmental

Ambient Air Temperature:	Operation -25 ... +70 °C
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Additional Information

Actuator Type:	Extended
Additional Information:	III. PB
Bezel Material:	Black plastic
Block:	1NO
Color:	Green
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
Function:	Momentary
Illumination:	Illuminated
Lamp Type:	LED 110-130V AC/DC
Lens Color:	Green
Lower Button Color:	Green
Mechanical Durability:	0.5 million
Number of Auxiliary Contacts NO:	1
Order Multiple:	1 piece
Product Main Type:	CP3
Product Name:	Pushbutton
Product Range:	Compact
Product Type:	CP
Rated Frequency (f):	50 / 60 Hz
Rated Operational Current AC-15 (I _e):	(240 V) 1 A (120 V) 1.5 A
Rated Operational Current DC-13 (I _e):	(125 V) 0.2 A (24 V) 0.3 A
Rated Operational Voltage:	110...130 V AC/DC
RoHS Date:	0626 5

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SFC151004C0201
Declaration of Conformity - CE:	1SFA1-70
RoHS Information:	1SFC151012D0202

Classifications

E-nummer:	3717266
ETIM 4:	EC002024 - Accessories for control circuit devices
ETIM 5:	EC002024 - Accessories for control circuit devices
Object Classification Code:	S