



Electric Automation
Automation specialists

Reference: RB121A 24VAC/DC
Code: 1SNA645005R0700

RB121A-24VAC/DC Interface relay R600 1c/o,A1-A2=24VAC/DC,250V/1mA-6A,LED

[Buy it at Electric Automation Network](#)



Screw relay RB121A 24vac/dc : 24vac-dc input / 1SPDT 1 mA upto 6A with led

Ordering

EAN:	4013614507762
Minimum Order Quantity:	10 piece
Customs Tariff Number:	85364900

Dimensions

Product Net Width:	6 mm
Product Net Height:	67.5 mm
Product Net Depth:	70 mm
Product Net Weight:	0.02 kg

Container Information

Package Level 1 Units:	10 piece
Package Level 1 Width:	73 mm
Package Level 1 Height:	71 mm
Package Level 1 Length:	80 mm
Package Level 1 Gross Weight:	0.23 kg

Package Level 1 EAN:	3472596450052
----------------------	---------------

Technical

Function:	Boxed interface relay R600
Sub-Function:	Relay with built in LED
Output:	1 c/o (SPDT) contact
Output Signal:	5 ... 250 V AC / 1 mA ... 6 A
Rated Control Supply Voltage (U _s):	24 V AC/DC
Terminal Type:	Screw Terminals

Certificates and Declarations (Document Number)

CSA Certificate:	CSA_254821
cUR Certificate:	cUR_E352056
Declaration of Conformity - CE:	1SND225042C1000
EAC Certificate:	EAC_RU_C-FR.ME77.B.01634
LR Certificate:	LRS_0620042
UR Certificate:	UR_E352056

Classifications

Object Classification Code:	K
ETIM 4:	EC001437 - Switching relay
ETIM 5:	EC001437 - Switching relay
UNSPSC:	39121500
eClass:	7.0 27371601