



Electric Automation
Automation specialists

Reference: RBR 122 A-230VAC/D
Code: 1SNA645513R2000

RBR122A-230VAC/DC Interface relay
R600 2c/o,A1-A2=230VAC/
DC,250V/1mA-8A

Buy it at Electric Automation Network



Spring relay RBR122A 230vac/dc : 230vac-dc input / 1DPDT 1 mA upto 8A with led

Ordering

EAN:	4013614508271
Minimum Order Quantity:	5 piece
Customs Tariff Number:	85364900

Dimensions

Product Net Width:	12 mm
Product Net Height:	67.5 mm
Product Net Depth:	75 mm
Product Net Weight:	0.04 kg

Container Information

Package Level 1 Units:	5 piece
Package Level 1 Width:	73 mm
Package Level 1 Height:	71 mm
Package Level 1 Length:	80 mm
Package Level 1 Gross Weight:	0.24 kg

Package Level 1 EAN:	3472596455132
----------------------	---------------

Technical

Function:	Boxed interface relay R600
Sub-Function:	Relay with built in LED
Output:	2 c/o (SPDT) contacts
Output Signal:	5 ... 250 V AC / DC / 1 mA ... 8 A
Rated Control Supply Voltage (U _s):	230 V AC/DC
Terminal Type:	Spring Terminals

Certificates and Declarations (Document Number)

CSA Certificate:	CSA_254821
cUR Certificate:	cUR_E352056
Declaration of Conformity - CE:	1SND225049C1000
EAC Certificate:	EAC_RU_C-FR.ME77.B.01634
LR Certificate:	LRS_0620042
UR Certificate:	UR_E352056

Classifications

Object Classification Code:	K
ETIM 4:	EC001437 - Switching relay
ETIM 5:	EC001437 - Switching relay
UNSPSC:	39121500
eClass:	7.0 27371601